

DIRECTIONAL YAGI ANTENNAS

Y(B)8966

GOLD SERIES DIRECTIONAL YAGI ANTENNAS PROVIDE INDUSTRY-LEADING DESIGN FEATURES WITH LONG TERM OPTIMAL PERFORMANCE

Laird premium series directional Yagi antennas are fully gold anodized for corrosion resistance. All UHF and above frequency antennas feature internal matching to assure broad bandwidth and resistance to severe weather conditions. There is no gamma match to ice up, corrode or detune. Our engineering staff has optimized the product family for forward gain by computer analysis and then field-tested each for conformance.


FEATURES AND BENEFITS:

- All UHF and higher frequency antennas feature 360° welds around each element and an end-of-boom N connector feed with an internal transmission line feeding the driven element.
- Every Yagi is tuned on a network analyzer for best power match and lowest VSWR.
- All Yagi antennas ship complete with a high quality cast aluminum mounting kit that includes stainless steel hardware and allows vertical or horizontal orientation during installation (VHF models require light assembly).


APPLICATIONS:

- Point-to-point and multi-point / omnidirectional outdoor antennas applications used by private organizations and government agencies around the globe.
- Typical applications include transportation such as railroad switching, remote locations reporting examples that include oil fields, weather conditions and, meter data transmissions for utilities.

Electrical		Mechanical	
Frequency Range	896 – 970 MHz	Material	Aluminum
Frequency Bandwidth	74 MHz	Length	27.688"
VSWR	< 2:1	Height	6.75"
Return Loss	-10 dB max	Boom Diameter	.875"
Nominal Gain	9 dBd	Weight	3.9 lbs
Front to Back Ratio	20 dBd	Rated Wind Velocity	150 mph (241 kph)
Maximum Power	300 W	Rated Wind Velocity (with 0.5" radial ice)	80 mph (130 kph)
Nominal Impedance	50 Ω	Equivalent Flat Area	0.2492 sq. ft.
Polarization	Vertical or Horizontal	Cable	None
Pattern	Directional	Termination	N-Female connector
Horizontal Beamwidth (For Horizontal Polarization)	56°	Color	Gold or Black Anodized
Vertical Beamwidth (For Vertical Polarization)	52°	Lightning Protection	Lightning Arrestor LABH350NN (Sold Separately)
Tuning	Fixed	Mounting Included	Heavy duty cast aluminum bracket accommodates up to 2-1/2" mast
Transmitting/Receiving	Both		



Vertical-to-Vertical Polarization Azimuthal Pattern (Y, Z, or E-plane)



Horizontal-to-Horizontal Polarization Azimuthal Pattern (Y, Z, or H-plane)

ANT-DS-Y(B)8966 1015

Americas: +1.847.839.6907
IAS-AmericasEastSales@lairdtech.com

Europe: +44.1628.858941
IAS-EUSales@lairdtech.com

Asia: +86.21.5855.0827.127
IAS-AsiaSales@lairdtech.com

www.lairdtech.com

Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird shall not be liable for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2015 Laird Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trade marks or registered trade marks of Laird Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[Y8966](#)