


COAXIAL CONNECTOR, BNC, 50 Ohm, Straight panel cable jack (female), flange mount

25_BNC-50-2-15/133_N

Properties

- Useful for frequently coupled and uncoupled connections
- Available for 50 ohm and 75 ohm applications
- Applicable in frequencies up to 4 GHz



Product configuration

Gender	Standard
jack	IEC 60169-8_MIL-STD-348A/301_CECC 22120

Interface and material data

Piece parts	Material	Plating
Centre contact	Copper Beryllium / Brass	Gold Plating (Nickel underplated)
Outer conductor	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Crimp ferrule	Copper	SUCOPLATE (R) Plating

Electrical data

Impedance	50 Ω
Interface frequency	4 GHz

Mechanical data

Weight	0.0158 kg
Mating cycles	500
Cable entry centre contact	crimped
Cable entry outer contact	crimped

Environmental data

Operation temperature	-65 °C ... 165°C
-----------------------	------------------

Ordering Information Table

Item number	Item description	Packaging type
22641794	25_BNC-50-2-15/133_NE	Single
22650210	25_BNC-50-2-15/133_NH	Bulk 100 pcs

COAXIAL CONNECTOR, BNC, 50 Ohm, Straight panel cable jack (female), flange mount

25_BNC-50-2-15/133_N

Suitable cables	
Cable group	U4 - 2 mm / 50 Ohm
Suitable cables	ENVIROFLEX_316_D
	K_02252_D
	G_02232_D

Additional Information	
Only as assembly	No

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P2508 / Date of publication: 25.11.2023 / uncontrolled copy