


Features

- Peak breakdown voltage:
400V: BL52X; 600V: BL55X
- High isolation voltage between input and output (Viso =5000V rms)
- Operating Temperature: -55°C~100°C

HF




Applications

- Switching power supply, intelligent meter
- Industrial control, measuring instruments
- Office equipment such as copiers
- Household appliances: such as air conditioners, fans, water heaters, etc

Mechanical Data

- Case: DIP-4L, DIP-4L(M),SMD-4L
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208



Ordering Information

BL 5VX (M) (G) - (U) (N) (Y)

① ② ③ ④ ⑤ ⑥ ⑦


- ① Brand(BL)
- ② Product series(V:2,5; X:0,1,2,3,4)
- ③ Package type(DIP-4L:None, DIP-4L(M):M,SMD-4L:S)
- ④ Halogen option(None :Halogen free)
- ⑤ Lead frame (None: Copper)
- ⑥ Customer option 1 (0-9 or A-Z or none)
- ⑦ Customer option 2 (0-9 or A-Z or none)

Part Number	Package	Shipping Quantity	Marking Code
BL5V ¹ X ²	DIP-4L	100 pcs / Tube	BL5V ¹ X ²
BL5V ¹ X ² M	DIP-4L(M)	100 pcs / Tube	BL5V ¹ X ²
BL5V ¹ X ² S	SMD-4L	2000 pcs / Tape & Reel	BL5V ¹ X ²

Notes 1: V denotes V_{DRM} digits: 2, 5.
2: X denotes I_{FT} digits: 0, 1, 2, 3, 4.

Marking Information

- "BL" denotes brand
- "V" denotes V_{DRM} digits: 2, 5
- "X" denotes I_{FT} digits: 0, 1, 2, 3, 4
- "Y" denotes Year : A(2024), B(2025), C(2026)
- "WW" denotes Week's number
- "N" denotes the day of Week



Maximum Ratings (@ $T_A = 25^{\circ}\text{C}$ unless otherwise specified)

Parameter		Symbol	Value	Unit
Input	Forward Current	I_F	60	mA
	Reverse Voltage	V_R	6	V
	Power Dissipation	P_D	100	mW
	Power dissipation derating factor (above $T_a = 90^{\circ}\text{C}$)	P_{DD}	3.8	mW/ $^{\circ}\text{C}$
Output	Power Dissipation	P_C	300	mW
	Power dissipation derating factor (above $T_a = 90^{\circ}\text{C}$)		7.4	mW/ $^{\circ}\text{C}$
	Off-state Output Terminal Voltage	V_{DRM}	400	V
			600	
	Peak repetitive surge current (pw=100 μs , 120pps)	I_{TSM}	1	A
	Turn-on current (root mean square value)	$I_{T(RMS)}$	100	mA

Thermal Characteristics

Parameter	Symbol	Value	Unit
Total Power Dissipation	P_{TOT}	330	mW
Isolation Voltage ^{*1}	V_{ISO}	5000	Vrms
Operating Temperature	T_{OPR}	-55 ~ +100	$^{\circ}\text{C}$
Storage Temperature Range	T_{STG}	-55 ~ +125	$^{\circ}\text{C}$
Soldering Temperature ^{*2}	T_{SOL}	260	$^{\circ}\text{C}$

Notes:

- 40 to 60% RH, AC for 1 minute. At this time, pins 1, 2 & 3 are shorted, and pins 4, 5 & 6 are shorted together.
- For 10 seconds

Electrical Characteristics (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter			Symbol	Test Condition	Min.	Typ.	Max.	Unit
Input	Forward Voltage		V_F	$I_F=20\text{mA}$	-	1.24	1.5	V
	Reverse Leakage current		I_R	$V_R=6\text{V}$	-	-	10	μA
Output	Peak Blocking Current		I_{DRM}	$V_{\text{DRM}}=\text{Rated } V_{\text{DRM}}, I_F=0\text{mA}$	-	-	100	nA
	Peak on-state voltage		V_{TM}	$I_{\text{TM}}=100\text{mA}, I_F=\text{Rated } I_{\text{FT}}$	-	-	2.5	V
	Critical Rate of Rise off-state Voltage	BL52X	dv/dt	$V_{\text{PEAK}}=\text{Rated } V_{\text{DRM}}, I_F=0\text{mA}$	-	100	-	V/ μs
		BL55X			1000	-	-	
Transfer Characteristics	LED trigger current	BL520	I_{FT}	Main terminal voltage = 3V	-	20	30	mA
		BL521			-	10	15	
		BL551			-	5	10	
		BL522			-	3	5	
		BL552			-	2	3	
		BL523			-	-	-	
		BL553			-	-	-	
		BL524			-	-	-	
		BL554			-	-	-	
	Holding Current		I_H	-	-	250	-	μA

Ratings and Characteristics Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Fig.1 LED Positive voltage vs Positive current




Fig.2 On-state characteristic




Fig.3 Trigger current vs Ambient temperature




Fig.4 LED Trigger current vs LED Pulse Width




Fig.5 Holding current vs Temperature




Fig.6 Leakage current vs Temperature





Fig.7 Static dv / dt test circuit and waveform



The high voltage pulse applied to the output of the device under test through the RC circuit is set to the required V_{PEAK} value. LED current is not applied. The waveform V_T is monitored with X100 probe. By adjusting the R_{TEST} value, the dv/dt (slope) increases until the device under test is observed to be triggered (waveform collapse). Then dv/dt drops until the device under test stops being triggered. At this point, τ_{RC} is recorded and the dv/dt calculated.


$$dv/dt = \frac{0.632 \times V_{PEAK}}{\tau_{RC}}$$

For example, $V_{PEAK} = 400V$ for QX302X series. The dv/dt value is calculated as follows:


$$dv/dt = \frac{0.632 \times 400}{\tau_{RC}} = \frac{252}{\tau_{RC}}$$

Package Outline Dimensions (unit: mm)


DIP-4L




DIP-4L(M)




SMD-4L



SOLDERING FOOTPRINT (unit: mm)



Reflow soldering




	Symbol	Min	Max	Unit
Preheat temperature	Ts	150	200	°C
Preheat time	ts	60	120	s
Ramp-up rate(T _L to T _P)			3	°C/s
Liquidus temperature	T _L	217		°C
Time above T _L	t _L	60	150	s
Peak temperature	T _P		260	°C
Time during which T _c is between (T _P -5) and T _P	t _p		30	s
Ramp-down rate(T _P to T _L)			6	°C/s

Note:

Reflow soldering is recommended at the temperatures and times shown, no more than three times.

Wave soldering



Profile feature	
Average ramp-up rate	~200°C/s
Heating rate during preheat	1°C/s to 2°C/s typical; 4°C/s maximum
Final preheat temperature Ts	~130°C
Preheat time (25°C to Ts)	>60s
Peak temperature Tp	260°C
Time within peak temperature tp	10s
Ramp-down rate	5°C/s maximum

Soldering with hand soldering iron

- Hand soldering iron is only used for product rework or sample testing.
- Hand soldering iron requirements: Temperature: 360 °C ± 5°C within 3s.

Pcaking

Package Type	Packing Form	Quantity per Tube &Reel	Quantity per Box	Quantity per Carton	Antistatic Bag Specification	Box Specification	Carton Specification	Note
DIP-4L	Tube(500mm)	100 pcs/tube	25 tubes /box	12 boxes /ctn	190*670mm	520*105*50mm	545*372*235mm	Straight insert type material tube
DIP-4L(M)	Tube(500mm)	100 pcs/tube	25 tubes /box	12 boxes /ctn	190*670mm	520*105*50mm	545*372*235mm	Seagull foot (M foot) tube
SMD-4L	Reel(φ330mm)	2000 pcs/reel	2 reels /box	5 boxes /ctn	380*420mm	350*340*60mm	365*330*370mm	Guard band 200mm /min.


■Summary table

■ DIP-4L/ DIP-4L(M) (Tube)

Qty/ tube : 100 pcs. Qty/box: 2500 pcs.

Qty/ctn : 30000 pcs.

Schematic: (unit:mm)





■SMD-4L (Reel)

Qty/reel: 2000 pcs. Qty/box: 4000 pcs.

Qty/ctn : 20000 pcs.

Schematic: (unit:mm)





IMPORTANT NOTICE

Galaxy Microelectronics (GME) reserves the right to make changes without further notice to any product herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.