

1008160

https://www.phoenixcontact.com/us/products/1008160

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Spacer sleeve for M23 Hybrid cable connectors from the SH series. Note: The item may only be used in the corresponding PxC products SH-8E..., SB-8E...9L...

Commercial data

Item number	1008160
Packing unit	100 pc
Minimum order quantity	100 pc
Sales key	AB33
Product key	ABRCDU
GTIN	4055626689579
Weight per piece (including packing)	0.937 g
Weight per piece (excluding packing)	0.894 g
Customs tariff number	39269097
Country of origin	DE

1008160

https://www.phoenixcontact.com/us/products/1008160



Technical data

Notes

Safety note

Safety note

WARNING: The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property.

- WARNING: Commission properly functioning products only.
 The products must be regularly inspected for damage.
 Decommission defective products immediately. Replace damaged products. Repairs are not possible.
- WARNING: Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product.
- The products are suitable for applications in plant, controller, and electrical device engineering.
- When operating the connectors in outdoor applications, they must be separately protected against environmental influences.
- Assembled products may not be manipulated or improperly opened.
- Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at phoenixcontact.com/products).
- When using the product in direct connection with third-party manufacturers, the user is responsible.
- For operating voltages > 50 V AC, conductive connector housings must be grounded
- Ensure that the protective or functional ground has been properly connected.
- VDE 0100/1.97 § 411.1.3.2 and DIN EN 60 204/11.98 § 14.1.3 are applicable when combining several circuits in a cable and/or connector.
- Only use tools recommended by Phoenix Contact
- The installation notes/Design In documents online on the download page at phoenixcontact.com/products must be observed for this product.
- Operate the connector only when it is fully plugged in and interlocked.
- Ensure that when laying the cable, the tensile load on the connectors does not exceed the upper limit specified in the standards.
- Observe the minimum bending radius of the cable. Lay the cable without twisting it.
- The connector warms up in normal operation. Depending on the ambient conditions, the surface of the connector can continue to warm up. In this case, the user is responsible for posting warnings (e.g. DIN EN ISO 13732-1:2008-12).



1008160

https://www.phoenixcontact.com/us/products/1008160

Product properties

Product type	Mounting material
Series	SH
Application	Hybrid
Thread type	M23

Material specifications

Housing material	Plastic

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-40 °C 115 °C
Ambient temperature (storage/transport)	15 °C 25 °C
Permissible humidity (storage/transport)	50 % 65 %



1008160

https://www.phoenixcontact.com/us/products/1008160

Classifications

UNSPSC 21.0

ECLASS

ECLASS-11.0	27440312
ECLASS-13.0	27440312
ECLASS-12.0	27440312
ETIM	
ETIM 9.0	EC002641
UNSPSC	

39121400





https://www.phoenixcontact.com/us/products/1008160

Environmental product compliance

EU RoHS

1008160

Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com