

Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of NXFT15XV103FA1B120 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=NXFT15XV103FA1B120

NXFT15XV103FA1B120










Appearance & Shape





Features

- 1. High accuracy and high sensibility temperature sensing is available by the small size and high accuracy NTC Thermistor.
- 2. Narrow space temperature sensing is available by the small sensing head and the thin lead wire.
- 3. You can choose the optimum length according to the design
- 4. This product is compatible with our 0402 (EIA) size chip Thermistor.
- 5. Excellent long time aging stability
- 6. This is halogen free product (CI= max.900ppm
- Br=max.900ppm and Cl+Br=max.1500ppm).
- 7. Lead is not contained in the product.
- 8. UL/cULcertified product.(UL1434, File No. E137188)



Applications

Limited Usage

Consumer Grade



Packaging Information

Packaging		Standard Packing Quantity
В	Bulk(Bag)	1000

1 of 3

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Product Search Data Sheet

Note: This datasheet may be out of date. $Please\ download\ the\ latest\ data sheet\ of\ NXFT15XV103FA1B120\ from\ the\ official\ website\ of\ Murata$ Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=NXFT15XV103FA1B120

NXFT15XV103FA1B120



Specifications

D 14 (05%)	101.0	
Resistance (25°C)	10kΩ	
Resistance Value Tolerance	±1%	
(at 25°C)		
B-Constant (25/50°C)	3936K	
B-Constant (25/50°C)	±1%	
Tolerance		
B-Constant(25/80°C)	3971K	
(Reference Value)		
B-Constant(25/85°C)	3977K	
(Reference Value)		
B-Constant(25/100°C)	3989K	
(Reference Value)		
Maximum Operating Current	0.12mA	
(25°C)		
Rated Electric Power (25°C)	7.5mW	
Typical Dissipation Constant	1.5mW/°C	
(25°C)		
Operating Temperature	-40°C to 125°C	
Range		
Thermal Time Constant	4s	
Lead Shape	Lead Wire type	
Size Code (in mm)	120 = 120mm	
Size Code (in inch)	120 = 120mm	
Shape	Lead	
Mass	0.12g	
MSL	N	

2 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Note: This datasheet may be out of date.


Please download the latest datasheet of NXFT15XV103FA1B120 from the official website of Murata Manufacturing Co., Ltd.


http://www.murata.com/en/products/productdetail?partno=NXFT15XV103FA1B120

NXFT15XV103FA1B120



Product Data





Resistance-Temperature Characteristics

Temperature Tolenrance VS. Temp.

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

