



CrossLink VIP Input Bridge Board

Evaluation Board User Guide

FPGA-EB-02002 Version 1.2

January 2018

Contents

Acronyms in This Document	3
1. Introduction	4
1.1. Further Information.....	4
2. Headers and Test Connections	6
3. Programming Circuit.....	7
4. CrossLink Interface Support.....	8
4.1. Camera Sensor Interface	8
4.2. Upstream Connector Interface.....	8
5. Power Supply	9
6. CrossLink I/O Ball Mapping to Connectors	10
7. Status Indicators	13
8. Ordering Information.....	14
References	15
Technical Support Assistance.....	15
Appendix A. CrossLink VIP Input Board Schematics	16
Appendix B. CrossLink VIP Input Bridge Board Bill of Materials	20
Revision History.....	25

Figures

Figure 1.1. Top View of CrossLink VIP Input Bridge Board and its Key Components.....	5
Figure 1.2. Bottom View of CrossLink VIP Input Bridge Board	5
Figure 3.1. Programming Block.....	7
Figure 4.1. Camera Sensor Interface.....	8
Figure 4.2. Upstream Connector Interface	8
Figure 5.1. Power Supply Block.....	9
Figure A.1. Block Diagram.....	16
Figure A.2. Power Regulator and Power Decoupling.....	17
Figure A.3. DPHY, Bank 1 and 2 Interface	18
Figure A.4. Board to Board Connector and Flash Interface	19

Tables

Table 2.1. Headers and Test Connectors	6
Table 5.1. Power LEDs.....	9
Table 5.2. Device Power Rail Summary and Test Points	9
Table 6.1. Upstream Connector Mapping.....	10
Table 6.2. Camera Sensor Connector Pin Mapping	12
Table 7.1. Status LED I/O Map	13
Table 8.1. Reference Part Number	14

Acronyms in This Document

A list of acronyms used in this document.

Acronym	Definition
CMOS	Complementary Metal-Oxide Semiconductor
CSI-2	Camera Serial Interface
DDR	Double Data Rate
DSI	Display Serial Interface
FTDI	Future Technology Devices International
GPIO	General Purpose Input/Output
I ² C	Inter-Integrated Circuit
LDO	Low Dropout
LVDS	Low-Voltage Differential Signaling
MIPI	Mobile Industry Processor Interface
SPI	Serial Peripheral Interface
VIP	Video Interface Platform
VTT	Tracking Termination Voltage

1. Introduction

This document describes the Lattice Semiconductor CrossLink™ Video Interface Platform (VIP) Input Bridge Board that supports bridging of Dual MIPI® CSI-2 to parallel interfaces. The board's key component is the Lattice CrossLink FPGA, which receives input from the dual on-board Sony IMX214 cameras, and bridges CSI-2 to parallel interfaces.

This board is designed to work with the Lattice VIP board interconnect system. Typically, this board will be connected to the ECP5 VIP Processor Board, which can be programmed for a wide range of video processing applications.

The content of this user guide includes descriptions of on-board jumper settings, programming circuit, a complete set of schematics, and bill of materials for CrossLink VIP input bridge board.

Key features of the Crosslink VIP input bridge board include:

- CrossLink FPGA
 - Dual 4-lane MIPI CSI-2 receiver interface
 - SPI flash configuration
 - 24-bit parallel interface
 - General Purpose Input/Output
- Programming Circuit
 - From external board through board to board connector
 - SPI external programmer using header
- Dual camera interface
 - Dual 4-lane MIPI CSI-2 transmitter interface

Figure 1.1 on the next page shows the top view of the CrossLink VIP input bridge board and its key components.

Figure 1.2 shows the bottom view of the board.

1.1. Further Information

For more information on boards and kits available for the VIP system, visit www.latticesemi.com/boards

For details about the CrossLink FPGA, refer to FPGA-DS-02007, [CrossLink Family Data Sheet](#).

Refer to [Appendix A](#) and [Appendix B](#) for the schematics and BOM of the CrossLink VIP input bridge board.




Figure 1.1. Top View of CrossLink VIP Input Bridge Board and its Key Components




Figure 1.2. Bottom View of CrossLink VIP Input Bridge Board

2. Headers and Test Connections

Figure 1.1 shows the top view of the CrossLink VIP input bridge board. Table 2.1 lists the headers and test connectors.

Table 2.1. Headers and Test Connectors

Part	Description	Setting
J23	Clock input source selection	1–2 (Internal Osc.), 2–3 (External SMA)
J28	Debug Header	—
J4	SPI Flash chip select	Short
J2	LIFMD6000 chip select	Short
J30	LIFMD6000 CRESET selection	1–2 (External RESET), 2–3 (GND), Open (Normal)
J29	External programming header	—

3. Programming Circuit

CrossLink can be programmed by external programmer by connecting it on Header J18 or through the SPI interface on upstream connector (J3) by using Lattice Diamond® programmer software.

Figure 3.1 shows the programming block of CrossLink VIP input bridge board.

The SPI interface is used to program both CrossLink and SPI Flash Memory. Jumpers J2 and J4 on CrossLink VIP input bridge board enable the programming of CrossLink and its flash, respectively, through external programmer in SSPI Mode. For MSPI Mode of CrossLink both jumper J2 and J4 must be shorted for the configuration.




Figure 3.1. Programming Block

4. CrossLink Interface Support

The CrossLink VIP input bridge board supports various onboard interfaces and external interfaces through board-to-board connectors. The sections below describe key onboard interfaces supported on CrossLink VIP input bridge board.

4.1. Camera Sensor Interface

Figure 4.1 shows the block diagram of dual camera sensor Interface. Sony's IMX214 camera sensor is used as camera input source on the camera sensor connectors. The data path interface between the camera sensor module is CSI-2. The cameras are configured using I²C interface by the external board through upstream connectors.




Figure 4.1. Camera Sensor Interface

4.2. Upstream Connector Interface

Figure 4.2 shows the block diagram of the upstream connector. The upstream connector acts as board-to-board connector and interfaces CrossLink VIP input bridge board to ECP5 VIP processor board for bridging applications. The interface between CrossLink device and the upstream connector is 24-bit parallel data and control interface.




Figure 4.2. Upstream Connector Interface

5. Power Supply

The power supply to the CrossLink VIP input bridge board is provided from board-to-board connectors (J1 and J3).

Figure 5.1 shows the power supply block of the CrossLink VIP input bridge board. The external board (ECP5 VIP processor board) must be connected to power source for the onboard regulators for normal operation and successful programming. The board-to-board connector provides 5 V, 3.3 V, 2.5 V power source to the board and the onboard regulators to generate remaining power rails. Each I/O and core voltage rail on the board is accessible by a test point on the board.




Figure 5.1. Power Supply Block

Table 5.1 shows the voltage rail and its associated status LED.

Table 5.1. Power LEDs

Voltage Rail	LEDs	Color
5V	D5	Green
3V3	D6	Green
A2V8	D3	Green
2V5	D1	Green
D1V8	D2	Green
D1.05V	D4	Green

Table 5.2 lists the board voltage rails, including the rail source voltage, test point number, and voltage on net.

Table 5.2. Device Power Rail Summary and Test Points

Net Name	Source Rail	Test Points	Voltage on Net (V)
5V0	—	—	5
3V3	3V3_EXT	5V	3.3
A2V8	5V	5V	2.8
2V5	5V	5V	2.5
D1V8	2V5	D1V8	1.8
D1.05V	2V5	D1.05V	1.05
VCC_CORE	5V	VCC_CORE	1.2
VCC_DPHY	VCC_CORE	VCC_DPHY	1.2

6. CrossLink I/O Ball Mapping to Connectors

Table 6.1. Upstream Connector Mapping

J1			J3		
Pin number on Connector	Net Name	Ball Number	Pin Number on Connector	Net Name	Ball Number
1	3V3_EXT	—	1	3V3_EXT, L12	—
2	3V3_EXT	—	2	5V	—
3	3V3_EXT	—	3	3V3_EXT, L12	—
4	3V3_EXT	—	4	5V	—
5	D12	D9	5	GND	—
6	D0	F9	6	5V	—
7	D13	D8	7	GPIO3	J6
8	D1	F8	8	GND	—
9	D14	J7	9	—	—
10	D2	G9	10	LED4	—
11	D15	H7	11	GND	—
12	D3	G8	12	—	—
13	D16	J5	13	LED2	—
14	D4	E9	14	GND	—
15	D17	H5	15	—	—
16	D5	E8	16	—	—
17	GND	—	17	GND	—
18	GND	—	18	—	—
19	GND	—	19	LED3	—
20	GND	—	20	GND	—
21	D18	E1	21	—	—
22	GND	—	22	2V5_EXT	—
23	D19	E2	23	GND	—
24	D6	H9	24	2V5_EXT	—
25	D20	J4	25	—	—
26	D7	H8	26	—	—
27	D21	H4	27	MCLK	H1
28	D8	F7	28	RESET	—
29	D22	J3	29	SISPI	F1
30	D9	E7	30	—	—
31	D23	H3	31	SPISO	J1
32	D10	J9	32	—	—
33	GND	—	33	CSSPIN	G1
34	D11	J8	34	GND	—
35	GND	—	35	CDONE	H2
36	GND	—	36	—	—
37	-	—	37	CRESETB	G2
38	GND	—	38	—	—
39	GPIO2	G6	39	—	—
40	GND	—	40	GND	—
41	LED1	—	41	SCL	F2
42	SDA2	—	42	—	—

Table 6.1. Upstream Connector Mapping (Continued)

J1			J3		
Pin number on Connector	Net Name	Ball Number	Pin Number on Connector	Net Name	Ball Number
43	GPIO4	H6	43	SDA	J2
44	SCL2	—	44	—	—
45	GPIO5	D1	45	—	—
46	CAM_RESET	—	46	GND	—
47	GPIO6	D2	47	—	—
48	SDA1	—	48	—	—
49	—	—	49	—	—
50	SCL1	—	50	—	—
51	—	—	51	—	—
52	—	—	52	GND	—
53	GND	—	53	—	—
54	GND	—	54	—	—
55	GND	—	55	GND	—
56	GND	—	56	—	—
57	2V5_EXT, L11	—	57	GND	—
58	2V5_EXT	—	58	GND	—
59	2V5_EXT, L11	—	59	GND	—
60	2V5_EXT	—	60	—	—

Table 6.2. Camera Sensor Connector Pin Mapping

CN1			CN2		
Pin number on Connector	Net Name	Ball Number	Pin number on Connector	Net Name	Ball Number
1	—	—	1	—	—
2	SLVS_CN_1	A2	2	SLVS_CN_2	A9
3	SLVS_CP_1	A1	3	SLVS_CP_2	A8
4	GND	—	4	GND	—
5	SLVS_3N_1	B4	5	SLVS_3N_2	C9
6	SLVS_3P_1	A4	6	SLVS_3P_2	C8
7	GND	—	7	GND	—
8	SLVS_1N_1	B3	8	SLVS_1N_2	B9
9	SLVS_1P_1	A3	9	SLVS_1P_2	B8
10	GND	—	10	GND	—
11	SLVS_0N_1	B2	11	SLVS_0N_2	A7
12	SLVS_0P_1	B1	12	SLVS_0P_2	B7
13	GND	—	13	GND	—
14	SLVS_2N_1	C2	14	SLVS_2N_2	A6
15	SLVS_2P_1	C1	15	SLVS_2P_2	B6
16	GND	—	16	GND	—
17	GND	—	17	GND	—
18	A2V8	—	18	A2V8	—
19	—	—	19	—	—
20	CAM_CLK1	—	20	CAM_CLK2	—
21	—	—	21	—	—
22	CAM_SDA1	—	22	CAM_SDA2	—
23	CAM_SCL1	—	23	CAM_SCL2	—
24	CAM_RST1	—	24	CAM_RST2	—
25	D1.05V	—	25	D1.05V	—
26	D1V8	—	26	D1V8	—
27	GND	—	27	GND	—
28	GND	—	28	GND	—
29	A2V8	—	29	A2V8	—
30	GND	—	30	GND	—

7. Status Indicators

The LED status indicators on the board show the application status. [Table 7.1](#) lists the status LED I/O map.

Table 7.1. Status LED I/O Map

Connector	LED	Net Name	Color
J1	R436	LED1	Green
J3	R437	LED2	Green
J3	R438	LED3	Green
J3	R439	LED4	Green

8. Ordering Information

This board is included as part of a kit, and not available as a separate item. The below part number is for reference only, so it is clear which board is described in this document. Please visit www.latticesemi.com/boards for the latest ordering information.

Table 8.1. Reference Part Number

Description	Ordering Part Number
CrossLink VIP Input Bridge Board	LIFMD-VIP-IB-EVN

References

For more information, refer to

- FPGA-DS-02007, [CrossLink Family Data Sheet](#).
- FPGA-UG-02015, [Lattice Embedded Vision Development Kit User Guide](#)
- FPGA-EB-02001, [ECP5 VIP Processing Board](#)
- FPGA-EB-02003, [HDMI VIP Output Bridge Board](#)

Technical Support Assistance

Submit a technical support case through www.latticesemi.com/techsupport.

Appendix A. CrossLink VIP Input Board Schematics




Figure A.1. Block Diagram




Figure A.2. Power Regulator and Power Decoupling




Figure A.3. DPHY, Bank 1 and 2 Interface




Figure A.4. Board to Board Connector and Flash Interface

Appendix B. CrossLink VIP Input Bridge Board Bill of Materials

Item	Reference	Qty	Part	PCB Footprint	Comments	Part Number	Manufacturer	Description
1	VCC_DPHY1, VCCIO1, GND1, VCCIO2, GND2, GND3, GND4, D1V8, 2V5, A2V8, 3V3, 5V0, D1.05V, VCC_CORE, VCCIO0, TP1	16	TP_S_40_63	tp_s_40_63	DNL	—	—	Square test point, 40 mil inner diameter, 63 mil outer diameter
2	CN1, CN2	2	24-5804-030-030-829+	245804030 030829	Module info in BAG & TAG	24-5804-030-030-829+	Kyocera / Sunny Optical	Sony IMX214 CSI Camera sensor
3	C1, C3, C5, C7, C10, C11, C15, C17	8	10 μ F	C0603	—	CL10X106MP8 NRNC	Samsung	CAP CER 10 μ F 10 V 20% X6S 0603
4	C2, C4, C6, C8, C9, C12, C16, C18	8	0.1 μ F	C0402	—	CL05A104MP5 NNNC	Samsung	Cap Ceramic 0.1 μ F 10 V X5R 20% SMD 0402 85C Paper T/R
5	C13, C37, C42, C50	4	100 nF	C0201	—	C0603X5R1C1 04K030BC	TDK	CAP CER 0.1 μ F 16 V X5R 0201
6	C14, C28, C31, C39, C44, C51	6	1 μ F	C0306	—	LLR185C70G1 05ME05L	Murata	CAP CER 1 μ F 4 V X7S 0306
7	C19	1	4700 pF	C0306	—	LLL185R71H47 2MA01L	Murata	CAP CER 4700 pF 50 V X7R 0306
8	C20, C21, C23	3	330 pF	C0201	—	GRM033R71H 331KA12D	Murata	CAP CER 330 pF 50 V X7R 0201
9	C22, C25, C26, C38, C43	5	1.5 nF	C0201	—	GRM033R71A 152KA01D	Murata	CAP CER 1500 pF 10 V X7R 0201
10	C24	1	5600 pF	C0201	—	GRM033R71A 562KA01D	Murata	CAP CER 5600 pF 10 V X7R 0201
11	C27	1	1000 pF	C0201	—	GRM033R61E 102KA01D	Murata	CAP CER 1000 pF 25 V X5R 0201
12	C29, C32	2	0.01 μ F	C0201	—	GRM033R61C 103KA12D	Murata	CAP CER 10000 pF 16 V X5R 0201
13	C30, C33, C35, C40, C45, C49	6	470 pF	C0201	—	GRM033R71C 471KA01D	Murata	CAP CER 470 pF 16 V X7R 0201
14	C34	1	1 μ F	C0402	—	GRM155R61C 105KA12D	Murata	CAP CER 1 μ F 16 V X5R 0402
15	C36	1	0.1 μ F	C0201	—	GRM033R61C 104KE84D	Murata	CAP CER 0.1 μ F 16 V X5R 0201

Item	Reference	Qty	Part	PCB Footprint	Comments	Part Number	Manufacturer	Description
16	C41, C46, C54, C179, C180	5	100 nF	C0402	—	885012205018	Wurth	CAP CER 0.1 μ F 10 V X7R 0402
17	C47, C57	2	0.1 μ F	C0402	—	885012205037	Wurth	CAP CERAMIC 0.1 μ F 16 V X7R 0402
18	C48	1	2200 pF	C0201	—	GRM033R71E222KA12D	Murata	CAP CER 2200 pF 25 V X7R 0201
19	D1, D2, D3, D4, D5, D6, D7, D8, D9, D10	10	Green	led_0603	—	LTST-C190KGKT	LITE-On INC	LED SUPER GREEN CLEAR 0603 SMD
20	J1, J3	2	ERF5-030-070-L-DV-K-TR	ERF5-030-070-L-DV-K-TR	—	ERF5-030-070-L-DV-K-TR	Samtec Inc	Conn High Speed Edge Rate Terminal Strip HDR 60 POS 0.5 mm Solder ST SMD T/R -
21	J2, J4	2	CON2	CON2	—	61300211121	Wurth	2 Positions Header, Unshrouded Connector 0.100" (2.54 mm) through Hole Gold
22	J22	1	73391-0060	73391-0060	—	73391-0060	Molex	Molex Straight 500 Through Hole SMA Connector, jack, Solder Termination
23	J23, J30	2	CON3	CON3	—	61300311121	Wurth	3 Positions Header, Unshrouded Connector 0.100" (2.54 mm) through Hole Gold
24	J28	1	CON6	HDR1X6	—	61300611121	Wurth	6 Positions Header, Unshrouded Connector 0.100" (2.54 mm) through Hole Gold
25	J29	1	CONN PWR 5x2-H	5X2_CONN	—	61301021121	Wurth	10 Positions Header, Unshrouded Connector 0.100" (2.54 mm) through Hole Gold
26	L7, L8, L9, L10, L11, L12	6	60 Ω 2.3 A	FB0603	—	742792602	Wurth	EMI Filter Beads, Chips & Arrays 60 Ω Power
27	Q1, Q2, Q3, Q4	4	MMBT2222A	SM_SOT23-3	—	MMBT2222A, 215	NXP Semiconductor	Bipolar Transistors - BJT NPN Gen Pur SS

Item	Reference	Qty	Part	PCB Footprint	Comments	Part Number	Manufacturer	Description
28	R1, R2, R3, R7, R8, R14, R24, R26, R27, R47, R56, R57, R58, R59, R434	15	1K	R0402	—	RMCF0402JT1 K00	Stackpole Electronics Inc	RES 1K Ω 1/16 W 5% 0402
29	R4	1	6.04K	R0603	—	ERA-3ARB6041V	Panasonic	RES SMD 6.04K Ω 0.1% 1/10 W 0603
30	R5, R6, R18, R19, R22, R29, R30, R31, R32, R33, R37, R38, R40, R45, R46, R50, R51, R53, R72, R73, R74, R75, R76, R77, R78, R79, R80, R81, R82, R83, R84, R85, R86, R87, R88, R89, R90, R91, R92, R93, R94, R95, R431, R433, R435	45	0	R0603	—	RC0603JR-070RL	Yageo	Res 1/10 W 0.0 Ω 5% 0603
31	R9	1	1.62K	R0603	—	RN731JTTD16 21B25	KOA Speer	Thin Film Resistors 1.62K Ω , 0603, 0.1%, 2 5 ppm, 63 mW, 50 V
32	R10, R11, R12, R13	4	1	R0603	—	CRCW06031R 00JNEAHP	Vishay/Dale	RES 1.0 Ω 0.25 W 5% 0603 SMD
33	R15, R16, R17	3	1	R0603	DNL	CRCW06031R 00JNEAHP	Vishay/Dale	RES 1.0 Ω 0.25 W 5% 0603 SMD
34	R20, R21, R34, R35, R39, R41, R42, R43, R65, R440, R441, R442, R443, R444, R445	15	4.7k	R0603	—	CRCW06034K 70FKEA	Vishay	Thick Film Resistors - SMD 1/10 W 4.7K Ω 1%
35	R36, R432	2	100K	R0402	—	RMCF0402JT1 00K	Stackpole Electronics Inc	RES 100K Ω 1/16 W 5% 0402
36	R44	1	30E	R0603	—	RC0603FR-0730RL	Yageo	RES SMD 30 Ω 1% 1/10 W 0603
37	R48, R49, R52	3	10K	R0603	—	RMCF0603JT1 0K0	Stackpole Electronics Inc	Res Thick Film 0603 10K Ω 5% 1/10 W ∇ 100 ppm/C Molded SMD Paper T/R
38	R54	1	1K	R0603	—	RC0603FR-071KL	Yageo	Res Thick Film 0603 1K Ω 1% 1/10 W ∇ 100 ppm/C
39	R60, R61, R62, R63	4	10K	R0603	—	ERJ-3EKF1002V	Panasonic	RES SMD 10K Ω 1% 1/10 W 0603
40	R138, R436, R437, R438, R439	5	330E	R0402	—	CRCW040233 0RFKED	Vishay / Dale	Thick Film Resistors - SMD 1/16 W 330 Ω 1%

Item	Reference	Qty	Part	PCB Footprint	Comments	Part Number	Manufacturer	Description
41	SW1	1	WAKE_UP	4psmd_switch	—	434153017835	Würth	SWITCH TACTILE SPST-NO 0.05 A 12 V
42	SW2, SW3	2	SYS_RST	4psmd_switch	—	434153017835	Würth	SWITCH TACTILE SPST-NO 0.05 A 12 V
43	TH1, TH2, TH3, TH4	4	ThruHole	MTG125	DNL	—	—	—
44	U1	1	LTC3025-2	LTC3025-DFN	—	LTC3025EDC-2#PBF	Linear Tech	LDO Regulator Pos 1.2 V 0.5 A 6-Pin DFN EP T/R
45	U2	1	LTC3025-4	LTC3025-DFN	—	LTC3025EDC-4#PBF	Linear Tech	LDO Regulator Pos 1.8 V 0.5 A 6-Pin DFN EP T/R
46	U3	1	LTC3025-1	LTC3025-DFN	—	LTC3025EDC-1#PBF	Linear Tech	LDO Regulator 0.5 A 6-Pin DFN EP T/R
47	U4	1	LIFMD6000-csfBGA81	LIFMD6000-csfBGA81	—	LIFMD6000-csfBGA81	Lattice Semiconductor	Lattice semiconductor 6K CrossLink family FPGA
48	U5	1	LTC3025-1	LTC3025-DFN	—	LTC3025EDC-1#PBF	Linear Tech	LDO Regulator 0.5 A 6-Pin DFN EP T/R
49	U7	1	5PB1102PGGI	5PB1102PGGI	—	5PB1102PGGI	IDT,-Integrated-Device-Technology-Inc	Clock Fanout Buffer (Distribution) IC 200 MHz 8-TSSOP (0.173", 4.40 mm Width)
50	U9	1	M25PX16-VMW6TG	SOIC8	—	M25PX16-VMW6TG	Micron Technology Inc	IC FLASH 16 Mbit 75 MHz 8SO
51	U11, U12	2	FDC6301N	FDC6301N	—	FDC6301N	ON Semiconductor/Fairchild	Mosfet Array 2 N-Channel (Dual) 25 V 220 mA 700 mW Surface Mount SuperSOT™-6
52	U13	1	NC7WZ07P6X	NC7WZ07P6X	—	NC7WZ07P6X	Fairchild Semiconductor Corporation	IC BUFF DL UHS O/DRAIN SC70-6
53	X1	1	ASE3-27.000MHz-K-T	27MHZ	—	ASE3-27.000MHz-K-T	ABRACON	Standard Clock Oscillators 27.000 MHz 1.8 V 30 ppm

Item	Reference	Qty	Part	PCB Footprint	Comments	Part Number	Manufacturer	Description
54	X4	1	KC3225A27.00 00C30E0A	27MHZ_ OSC	—	KC3225A27.00 00C30E0A	AVX Corporation	Standard Clock Oscillators 27.000 MHz
55	CrossLink Video Processing Input Board Rev B PCB	1	—	—	—	305-PD-16- 0XXX	PACTRON	—

Revision History

Date	Version	Change Summary
January 2018	1.2	- Changed CrossLink pASSP to CrossLink FPGA in the Introduction section and the Further Information section. - Updated Lattice Semiconductor Logo on the cover pages, headers, and footers of this document.
June 2017	1.1	Updated Ordering Information section.
April 2017	1.0	Initial release.



7th Floor, 111 SW 5th Avenue
Portland, OR 97204, USA
T 503.268.8000
www.latticesemi.com