

1326510

https://www.phoenixcontact.com/us/products/1326510

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sleeve housing B48, for single locking latch, material: Die-cast aluminum, salt water resistant, variable, height: 107.5 mm, cable gland: none, Standard

## Your advantages

• Good shielding in the event of electromagnetic interference

### Commercial data

| Item number                          | 1326510       |
|--------------------------------------|---------------|
| Packing unit                         | 1 pc          |
| Minimum order quantity               | 1 pc          |
| Sales key                            | BF56          |
| Product key                          | BF7APB        |
| GTIN                                 | 4063151617424 |
| Weight per piece (including packing) | 636 g         |
| Weight per piece (excluding packing) | 609.8 g       |
| Customs tariff number                | 85389099      |
| Country of origin                    | CN            |



1326510

https://www.phoenixcontact.com/us/products/1326510

### Technical data

#### Product properties

| Housing with locking latch |
|----------------------------|
| Sleeve housing             |
| Standard                   |
| B48                        |
| Tall design                |
| variable                   |
| none                       |
|                            |

#### Data management status

| Auticle periodes | 00 |
|------------------|----|
| Article revision | 00 |

#### **Dimensions**

| Dimensional drawing | 132 90   |
|---------------------|----------|
| Width               | 90 mm    |
| Height              | 107.5 mm |
| Length              | 132 mm   |

### Material specifications

| Housing material         | Die-cast aluminum, salt water resistant |
|--------------------------|---|
| Housing surface material | uncoated                                |

### Mechanical properties

Mechanical data

| Locking type | Pin |
|--------------|-----|

### Environmental and real-life conditions

#### Ambient conditions

| Degree of protection    | IP66        |
|-------------------------|-------------|
|                         | IP67        |
| Enclosure rating (NEMA) | 4 (UL 50e)  |
|                         | 4X (UL 50e) |
|                         | 12 (UL 50e) |
| Impact strength         | IK08        |





1326510

https://www.phoenixcontact.com/us/products/1326510

## Drawings

### Dimensional drawing





Dimensional drawing



1326510

https://www.phoenixcontact.com/us/products/1326510

### **Approvals**

🌣 To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/1326510



**cUL Recognized**Approval ID: E255026



**UL Recognized**Approval ID: E255026

cULus Recognized



1326510

https://www.phoenixcontact.com/us/products/1326510

### Classifications

UNSPSC 21.0

#### **ECLASS**

| ECLASS-11.0 | 27440202 |
|-------------|----------|
| ECLASS-12.0 | 27440202 |
| ECLASS-13.0 | 27440202 |
| ETIM        |          |
| ETIM 9.0    | EC000437 |
| UNSPSC      |          |

31261500



1326510

https://www.phoenixcontact.com/us/products/1326510

### Environmental product compliance

#### EU RoHS

| Fulfills EU RoHS substance requirements | Yes, No exemptions                       |
|---|--|
| China RoHS                              |  |
| Environment friendly use period (EFUP)  | EFUP-E                                   |
|   | No hazardous substances above the limits |
| EU REACH SVHC                           |  |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%               |

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com