

Our commitment. Your advantage.

Search

**Live Product Chat** 

**Check Pricing & Availability** 

Contact Us About This Product

**Product Feature Selector** 

Search for Tooling

**Quick Links** 

**Products** 

**Documentation** 

Resources

My Account

**Customer Support** 

<u>Home</u> > <u>Products</u> > <u>By Type</u> > <u>Resistors</u> > <u>Product Feature Selector</u> > <u>Product Details</u>

# **SBC1510RJP Product Details**



SBC1510RJP (1623740-4)TE Internal Number: 1623740-4 Active

#### **Fixed Resistors**

<u>Converted to EU RoHS/ELV Compliant (Statement of Compliance)</u>

#### **Product Highlights:**

- Resistor Type = Power Resistor
- Resistance Selection = <1K?
- Resistance = 10?
- Power Rating = 17.00 W
- Tolerance = 5 %

View all Features









#### **Documentation & Additional Information**

#### **Product Drawings:**

None Available

#### Catalog Pages/Data Sheets:

• <u>High Power Resistor - Type SBC (Square Ceramic) Seri...</u> (PDF, English)

#### **Product Specifications:**

None Available

#### **Application Specifications:**

• None Available

## **Instruction Sheets:**

None Available

## **CAD Files:**

None Available

## **Additional Information:**

• Product Line Information

## **Related Products:**

Tooling

List all Documents

# Product Features (Please use the Product Drawing for all design activity)

## **Product Type Features:**

- Resistor Type = Power Resistor
- <u>Resistance (?)</u> = 10
- <u>Element</u> = Wirewound
- <u>Termination Type</u> = Tinned Copper Leads

## **Electrical Characteristics:**

- Resistance Selection (?) = <1K
- Power Rating (W) = 17.00
- <u>Tolerance (%)</u> = 5
- <u>Package Type</u> = Loose Piece Box

## **Body Related Features:**

- <u>Series</u> = SBC
- Mount Style = Axial Leaded
- Package, Component Size = 9 x 9 x 75

# **Industry Standards:**

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Wave solder capable to 240?C, Wave solder capable to 260?C, Wave solder capable to 265?C
- RoHS/ELV Compliance History = Converted to comply with RoHS directive

## **Conditions for Usage:**

• Temperature Coefficient (ppm/?C) = ?400

## **Operation/Application:**

Application = Power

## Other:

• Brand = CGS