6-87961-4 ACTIVE

AMPMODU

TE Internal #: 6-87961-4


PCB Mount Receptacle, Right Angle, Board-to-Board, 130 Position, 2.54 mm [.1 in] Centerline, Header & Push-Push Assembly, Gold,

Through Hole - Solder

View on TE.com >



Connectors > PCB Connectors > PCB Headers & Receptacles



PCB Connector Assembly Type: PCB Mount Receptacle

PCB Mount Orientation: Right Angle Connector System: Board-to-Board

Number of Positions: 130

Number of Rows: 2

Features

Product Type Features

PCB Connector Assembly Type	PCB Mount Receptacle
Connector System	Board-to-Board
Header Type	Header & Push-Push Assembly
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Stackable	No
PCB Mount Orientation	Right Angle
Number of Positions	130
Number of Rows	2

Body Features

Connector Profile	Standard
Primary Product Color	Natural

Contact Features

Closed Entry Housing
.64 mm[.025 in]
1.27 μm[50 μin]
Short Point



PCB Contact Termination Area Plating Material	Gold Flash
Contact Base Material	Phosphor Bronze
Contact Mating Area Plating Material	Gold
Contact Mating Area Plating Material Thickness	1.27 μm[50 μin]
Contact Type	Socket
Contact Current Rating (Max)	3 A
Termination Features	
Rectangular Termination Post & Tail Thickness	.2 mm[.008 in]
Rectangular Termination Post & Tail Width	.69 mm[.027 in]
Termination Post & Tail Length	2.92 mm[.115 in]
Termination Method to PCB	Through Hole - Solder
Mechanical Attachment	
Mating Alignment	With
Mating Alignment Type	Guide Pins
PCB Mount Retention	Without
PCB Mount Alignment	With
Connector Mounting Type	Board Mount
Housing Features	
Mating Entry Location	Side
Centerline (Pitch)	2.54 mm[.1 in]
Housing Material	Polyphenylene Sulfide (PPS)
Dimensions	
Connector Height	6.05 mm[.238 in]
Row-to-Row Spacing	2.54 mm[.1 in]
PCB Thickness (Recommended)	1.57 mm[.062 in]
Usage Conditions	
Housing Temperature Rating	Standard
Operating Temperature Range	-65 – 125 °C[-85 – 257 °F]
Operation/Application	
Solder Process Feature	Board Standoff
Circuit Application	Signal
De also ation at Foots was	

Packaging Features



Packaging Quantity	15
Packaging Method	Tube

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Pin-in-Paste capable to 260°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Customers Also Bought














TE Part #2-1445093-4 MICRO MNL HDR ASSY S/ROW AU LF



TE Part #360040-1 110 FASTON HSG.,FLAG,REC.,1 POS, NATRUAL



TE Part #YDTS20F25-29SAV001 RECP ASSY

TE Part #6-1617802-2 HFW5A1230K01=HFW 5 AMP HALF SIZE RELAY

Documents

Product Drawings

130 MODII HORZ DR CE 100CL/115

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_6-87961-4_N.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_6-87961-4_N.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_6-87961-4_N.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

English

Japanese

AMPMODU Connectors and AMP Box Contact Connectors

English