



09 65 221 7703  
D-Sub - S PCB connector

Other applications

|                    |                                 |
|--------------------|---------------------------------|
| gender             | male connector, straight        |
| Termination        | Stamped solder pins             |
| shell              | tinned metal shell with dimples |
| Number of contacts | 15 way                          |
| Board fixing       | without grounding board locks   |
| flange             | with screw lock UNC 4-40        |
| Performance level  | Performance level 3             |
| Material           | PBTP                            |

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF

09 65 221 5703  
D-Sub - S PCB connector

Other applications

|                    |                                 |
|--------------------|---------------------------------|
| gender             | male connector, straight        |
| Termination        | Stamped solder pins             |
| shell              | tinned metal shell with dimples |
| Number of contacts | 15 way                          |
| Board fixing       | without grounding board locks   |
| flange             | with screw lock UNC 4-40        |
| Performance level  | Performance level S4            |
| Material           | PBTP                            |

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF

09 65 221 6703  
D-Sub - S PCB connector

Other applications

|                    |                                 |
|--------------------|---------------------------------|
| gender             | male connector, straight        |
| Termination        | Stamped solder pins             |
| shell              | tinned metal shell with dimples |
| Number of contacts | 15 way                          |
| Board fixing       | without grounding board locks   |
| flange             | with screw lock UNC 4-40        |
| Performance level  | Performance level 2             |
| Material           | PBTP                            |

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.



Data sheets are available in following formats  
2D files

Typenblatt

Typenblatt