

#### Product Search Data Sheet

Please download the latest datasheet of DLW5BSZ501TQ2# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=DLW5BSZ501TQ2%23

Note: This datasheet may be out of date.

"#" indicates a package specification code.

DLW5BSZ501TQ2#









< List of part numbers with package codes >

DLW5BSZ501TQ2B


DLW5BSZ501TQ2K

DLW5BSZ501TQ2L



## Appearance & Shape





# **Applications**



Infotainment



## Packaging Information

Packaging	Specifications	Standard Packing Quantity
В	Bulk(Bag)	100
K	330mm Embossed Tape	1500
L	180mm Embossed Tape	400



#### **Features**

- 1. Small size (5.0x5.0mm) and high rated current (0.7 to 1.5A)
- 2. High common mode Impedance (max 2800ohm, at 10MHz.)
- 3. Operating Temperature Range -40°C to +105°C

1 of 3

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





#### INOVATOR IN ELECTRONICS

DLW5BSZ501TQ2#

Note: This datasheet may be out of date.

Please download the latest datasheet of DLW5BSZ501TQ2# from the official website of Murata

http://www.murata.com/en-us/products/productdetail?partno=DLW5BSZ501TQ2%23

Manufacturing Co., Ltd.

### "#" indicates a package specification code.



## **Specifications**

Shape	SMD
Size Code (in mm)	5050
Size Code (in inch)	2020
Length	5.0mm
Length Tolerance	±0.3mm
Width	5.0mm
Width Tolerance	±0.3mm
Thickness	4.5mm
Thickness Tolerance	max.
Common Mode Impedance (at 100MHz)	500Ω
Common Mode Impedance (at 100MHz) Tolerance	(Тур.)
Common Mode Impedance (at 10MHz)	2800Ω
Common Mode Impedance (at 10MHz) Tolerance	±40%
Rated Current	700mA
Derating of Rated Current	No
Rated Voltage	50Vdc
Withstanding Voltage	125Vdc
DC Resistance(max.)	0.23Ω
DC Resistance	0.23Ω max.
Insulation Resistance(min.)	10ΜΩ
Operating Temperature Range	-40°C to 105°C
Mass(typ.)	0.3g
Number of Circuit	1

Operating Temperature	
Range(Self-temperature rise	No
is included)	

2 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.




Note: This datasheet may be out of date. Please download the latest datasheet of DLW5BSZ501TQ2# from the official website of Murata Manufacturing Co., Ltd.


http://www.murata.com/en-us/products/productdetail?partno=DLW5BSZ501TQ2%23

"#" indicates a package specification code.

# DLW5BSZ501TQ2#








Impedance-Frequency Characteristics

Impedance-Frequency Characteristics (Main Items)



**Equivalent Circuit** 

3 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

