

09 66 152 5612
D-Sub - S PCB connector

Other applications

gender	female connector, right angled
Termination	Stamped solder pins
shell	tinned metal shell
Number of contacts	9 way
Row pitch	Row separation 2.54 mm
Board fixing	with grounding board locks
flange	UNC4-40
Performance level	Performance level S4
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF

09 66 152 5611
D-Sub - S PCB connector

Other applications

gender	female connector, right angled
Termination	Stamped solder pins
shell	tinned metal shell
Number of contacts	9 way
Row pitch	Row separation 2.54 mm
Board fixing	with grounding board locks
flange	M 3
Performance level	Performance level S4
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.



Data sheets are available in following formats
2D files

Typenblatt

Typenblatt

09 66 152 6611
D-Sub - S PCB connector

Other applications

gender	female connector, right angled
Termination	Stamped solder pins
shell	tinned metal shell
Number of contacts	9 way
Row pitch	Row separation 2.54 mm
Board fixing	with grounding board locks
flange	M 3
Performance level	Performance level 2
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF

09 66 152 6612
D-Sub - S PCB connector

Other applications

gender	female connector, right angled
Termination	Stamped solder pins
shell	tinned metal shell
Number of contacts	9 way
Row pitch	Row separation 2.54 mm
Board fixing	with grounding board locks
flange	UNC4-40
Performance level	Performance level 2
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF

09 66 152 7611
D-Sub - S PCB connector

Other applications

gender	female connector, right angled
Termination	Stamped solder pins
shell	tinned metal shell
Number of contacts	9 way
Row pitch	Row separation 2.54 mm
Board fixing	with grounding board locks
flange	M 3
Performance level	Performance level 3
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF

09 66 152 7612
D-Sub - S PCB connector

Other applications

gender	female connector, right angled
Termination	Stamped solder pins
shell	tinned metal shell
Number of contacts	9 way
Row pitch	Row separation 2.54 mm
Board fixing	with grounding board locks
flange	UNC4-40
Performance level	Performance level 3
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF