




N = Number of poles
Dim A = N x 3.81
Dim B = (N-1) x 3.81

Poles	Dim A	Dim B
2-6p	±0.20	±0.15
7-12p	±0.25	±0.20
13-18p	±0.30	±0.25
19-24p	±0.35	±0.30



SIGN	DATE	DESCRIPTION	APPROVER
△	8/16'06	Added cULus standard	Steady
△	02/01'07	Part NO is change	Tason
△	08/28'12	Enlarge the chamfer to be 35 degree more	Guoxue
△	8/28'12	temperature changed from -30°C-105°C to -40°C-115°C	Guoxue
△	8/28'12	temperature changed from 250°C±10°C/5 Sec to 260°C±5°C/5 Sec	Guoxue
△	8/28'12	Add the tolerances	Guoxue
△	7/01'13	update the drawing	Guoxue

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material

- Item ① Terminal body (metal housing): Brass (CuZn) Ni plated
- △ ● Item ② Terminal screw: Steel Zinc plating "-" slot type
- Item ③ Contacts: Brass, Tin plated
- Item ④ Insulator (Cover): Thermoplastic (UL94V-0)
- Item ⑤ Insulator (Body): Thermoplastic (UL94V-0)

Electrical cULus

- Voltage rating: 300VAC
- Current rating: 10A
- Wire range:
- Solid wire (AWG): 16-28
- Stranded wire (AWG): 16-28
- Torque (Lb-In): 1.7
- Screw: M2
- Wire strip length: 5-6mm
- Withstanding Voltage: 1.6KV
- △ ● Operating temperature: -40°C to +115°C
- △ ● Soldering temperature: 260°C ± 5°C / 5 Sec
- Safety Approval: cULus
- Critical dimension: △

TV xx 31x 0 xxx G

02 2 poles	0 Black	000 0 Standard @ Logo	G: RoHS compliant
03 3 poles	5 Green (RAL6018/T)	000 A Standard ANY Logo	(lead < 4%)
~	6 Blue	Any special item by	In copper Alloy
	8 Grey (RAL 7035/D)	customer request,	
24 24 poles	C Green (RAL6018/U)	please contact sales	
		department.	

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE	TV-3.81mm Series								
PART NO.	TVxx31x0xxxxG				DWG NO.	8TV0101			
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.				Tolerance	
		Guoxue 2013.07.08	Guoxue 2013.07.08		UNIT: mm		X.	±0.50	
					SCALE: NONE		X.X	±0.30	
					REV.: G		X.XX	±0.10	
				SHEET: 01/01			X°	±1°	