

CHARACTERISSTICS

MATERIALS

HOUSING: BRASS

HOUSING PLATING: 196µ" NICKEL MIN. SHELL & COLLET NUT: BRASS, 196µ" CHROME PLATED MIN.

CONTACTS: COPPER ALLOY

CONTACT PLATING: 7µ" GOLD PLATED OVER 196µ" NICKEL MIN.

INSULATOR: PPS (HIGH TEMPERATURE)

STRAIN RELIEF(BOOT): THERMOPLASTIC POLYURETHANE

MECHANICAL

DURABILITY: 5000 CYCLES

OPERATING TEMP. RANGE: -40° C ~ +200° C PROCESS TEMPERATURE: 260°C FOR 5 SECONDS

MAX. TOURQUE VALUE: 0.5 Nm [4.4 IN/LBS]


SHIELDING: 75dB @ 10MHz 40dB @ 1GHz

IP RATING: 50

CHART B

COLLET SIZE	WIRE DIAMETER				
30	2.50 [0.098] ~ 3.20 [0.126]				
40	3.30 [0.130] ~ 4.20 [0.165]				
50	4.30 [0.169] ~ 5.20 [0.205]				

CHART A



2 POSITION 22 AWG MAX. 10 AMP MAX. PIN Ø = 0.90 [0.035]

CONTACT RESISTANCE = $6 \text{ m}\Omega$ TEST VOLTAGE = 1000V WORKING VOLTAGE = 330V





3 POSITION 22 AWG MAX. 8 AMP MAX. PIN Ø = 0.90 [0.035]

CONTACT RESISTANCE = $6 \text{ m}\Omega$ TEST VOLTAGE = 1200V WORKING VOLTAGE = 400V





4 POSITION 24 AWG MAX. 7 AMP MAX. PIN Ø = 0.70 [0.028]

CONTACT RESISTANCE = $7.5 \text{ m}\Omega$ TEST VOLTAGE = 850V WORKING VOLTAGE = 280V



5 POSITION 24 AWG MAX. 6.5 AMP MAX. PIN Ø = 0.70 [0.028]

CONTACT RESISTANCE = $7.5 \text{ m}\Omega$ TEST VOLTAGE = 850V WORKING VOLTAGE = 280V



6 POSITION 28 AWG MAX. 2.5 AMP MAX. PIN Ø = 0.50 [0.020]

CONTACT RESISTANCE = $10 \text{ m}\Omega$ TEST VOLTAGE = 850V WORKING VOLTAGE = 280V



VIEW FROM TERMINATION END

7 POSITION 28 AWG MAX. 2.5 AMP MAX. PIN Ø = 0.50 [0.020]

CONTACT RESISTANCE = $10 \text{ m}\Omega$ TEST VOLTAGE = 800V WORKING VOLTAGE = 260V



9 POSITION 28 AWG MAX. 2 AMP MAX. PIN Ø = 0.50 [0.020]

CONTACT RESISTANCE = $10 \text{ m}\Omega$ TEST VOLTAGE = 600V WORKING VOLTAGE = 200V

Rohs Compliant



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

NorComp

DRAWN: M. SIGMON	DATE: 02-02-16	SCALE: N.T.S.	SHEET 1	OF 1	REV:
			DWG NO. 820BYYY-273LYY1		