

SHELL SIZE				TABLE III								TABLE VI				REVISIONS			
A	F	L	S	H	E	F	G	H	P	R	S	T	SYM.	DESCRIPTION	DATE	APPROVED			
				MAX	MAX	MAX	MAX	MAX	MAX	MAX	MAX	MAX	SEE SHEET 1						
03	6	08	08	09	.457(11.6)	1.674(42.5)	.500(12.7)	1.684(42.8)	.81(20.57)	1.03(26.26)	.69(17.53)	.96(24.38)							
08		10	10	11	.520(13.2)	1.734(44.0)	.590(15.1)	1.804(45.8)	.91(23.11)	1.91(48.77)	.78(19.81)	1.78(45.21)							
10		12	13	13	.582(14.8)	1.794(45.6)	.610(15.5)	1.824(46.3)	.97(24.64)	1.97(50.04)	.81(20.57)	1.81(45.97)							
12		14	15	14	.645(16.4)	1.884(47.9)	.700(17.8)	1.894(48.1)	1.03(26.16)	2.03(50.56)	.83(21.08)	1.83(46.48)							
14		16	17	15	.738(18.7)	1.994(50.6)	.885(22.5)	1.984(50.4)	1.09(27.68)	2.09(53.09)	.85(21.59)	1.85(46.99)							
16		18	18	17	.738(18.7)	1.994(50.6)	.885(22.5)	1.984(50.4)	1.15(29.21)	2.15(54.61)	.88(22.35)	1.88(47.75)							
18		20	19	19	.926(23.5)	2.184(55.5)	.975(24.8)	2.154(54.7)	1.20(30.48)	2.20(55.88)	.90(22.86)	1.90(48.26)							
20		22	20	21	.926(23.5)	2.184(55.5)	.975(24.8)	2.154(54.7)	1.27(32.26)	2.27(57.66)	.93(23.62)	1.93(49.02)							
22		24	22	23	1.020(25.9)	2.334(59.3)	1.125(28.6)	2.264(57.5)	1.33(33.78)	2.33(59.18)	.95(24.13)	1.95(49.02)							
24		26	24	25	1.020(25.9)	2.334(59.3)	1.125(28.6)	2.264(57.5)	1.39(35.31)	2.39(60.71)	.98(24.89)	1.98(50.29)							
26		28	26	27	1.145(29.1)	2.384(60.6)	1.225(31.1)	2.434(61.8)	1.46(37.08)	2.46(62.48)	1.15(29.21)	2.15(54.61)							
28		30	28	29	1.207(30.7)	2.484(63.1)	1.275(31.1)	2.684(68.2)	1.59(40.38)	2.59(65.79)	1.21(30.73)	2.21(56.13)							
30		32	30	31	1.238(31.4)	2.574(65.4)	1.275(31.1)	2.684(68.2)	1.69(42.93)	2.69(68.33)	1.24(31.50)	2.24(56.90)							
32		34	32	33					1.27(32.26)	1.49(37.85)	.88(22.35)	1.10(27.94)							
34		36	34	35															
36		38	36	37															
38		40	38	39															
40		42	40	41															
42		44	42	43															
44		46	44	45															
46		48	46	47															
48		50	48	49															
50		52	50	51															
52		54	52	53															
54		56	54	55															
56		58	56	57															
58		60	58	59															
60		62	60	61															
62		64	62	63															
64		66	64	65															
66		68	66	67															
68		70	68	69															
70		72	70	71															
72		74	72	73															
74		76	74	75															
76		78	76	77															
78		80	78	79															
80		82	80	81															
82		84	82	83															
84		86	84	85															
86		88	86	87															
88		90	88	89															
90		92	90	91															
92		94	92	93															
94		96	94	95															
96		98	96	97															
98		100	98	99															
100		102	100	101															
102		104	102	103															
104		106	104	105															
106		108	106	107															
108		110	108	109															
110		112	110	111															
112		114	112	113															
114		116	114	115															
116		118	116	117															
118		120	118	119															
120		122	120	121															
122		124	122	123															
124		126	124	125															
126		128	126	127															
128		130	128	129															
130		132	130	131															
132		134	132	133															
134		136	134	135															
136		138	136	137															
138		140	138	139															
140		142	140	141															
142		144	142	143															
144		146	144	145															
146		148	146	147															
148		150	148	149															
150		152	150	151															
152		154	152	153															
154		156	154	155															
156		158	156	157															
158		160	158	159															
160		162	160	161															
162		164	162	163															
164		166	164	165															
166		168	166	167															
168		170	168	169															
170		172	170	171															
172		174	172	173															
174		176	174	175															
176		178	176	177															
178		180	178	179															
180		182	180	181															
182		184	182	183															
184		186	184	185															
186		188	186	187															
188		190	188	189															
190		192	190	191															
192		194	192	193															
194		196	194	195															
196		198	196	197															
198		200	198	199															
200		202	200	201															
202		204	202	203															
204		206	204	205															
206		208	206	207															
208		210	208	209															
210		212	210	211															
212		214	212	213															
214		216	214	215															
216		218	216	217															
218		220	218	219															
220		222	220	221															
222		224	222	223															
224		226	224	225															
226		228	226	227															
228		230	228	229															
230		232	230	231															
232		234	232	233															
234		236	234	235															
236		238	236	237															
238		240	238	239															
240		242	240	241															
242		244	242	243															
244		246	244	245															
246		248	246	247															
248		250	248	249															
250		252	250	251															
252		254	252	253															
254		256	254	255															
256		258	256	257															
258		260	258	259															



Reference Information Standard Materials and Finishes

TABLE II - STANDARD FINISHES

GLENAIR SYMBOL	M85049 SYMBOL REFERENCE ONLY	FINISH	SPECIFICATION(S)
A		Cadmium Plate, Bright	AMS-QQ-P-416, Type I, Class 2
B		Cadmium Plate, Olive Drab	AMS-QQ-P-416, Type II, Class 3
C*	A	Anodize, Black	AMS-A-8625, Type II, Class 2
G*		Hard Coat, Anodic	AMS-A-8625, Type III, Class 1
J		Iridite, Gold Over Cadmium Plate Over Electroless Nickel	MIL-C-5541, Class 3 AMS-QQ-P-416, Type II, Class 3 over AMS-C-26074, Class 4, Grade B
LF		Cadmium Plate, Bright Over Electroless Nickel	1000 Hour Corrosion Resistance
M	N	Electroless Nickel	AMS-C-26074, Class 4, Grade B
N		Cadmium Plate, Olive Drab Over Electroless Nickel	AMS-QQ-P-416, Type II, Class 3 over Electroless Nickel AMS-C-26074
NC		Zinc Cobalt, Dark Olive Drab	96 Hour Corrosion Resistance
NF	W	Cadmium Plate, Olive Drab Over Electroless Nickel	1000 Hour Corrosion Resistance
T		Cadmium Plate, Bright Over Electroless Nickel	AMS-QQ-P-416, Type I, Class 3 ASTMB 733-90, SC2, Type I, Class 5, MIL-C-26074***
U		Cadmium Plate, Black	AMS-QQ-P-416, Type II, Class 3
ZU**		Cadmium Plate, Black	AMS-QQ-P-416, Type II, Class 3
ZN		Zinc-Nickel Alloy, Olive Drab	ASTMB 841-91, Over Electroless Nickel 1000 Hour Salt Spray

* Anodize finish; not suitable for EMI Shielding or grounding applications.
 ** Applicable to corrosion resisting steel backshells and accessories. Consult factory for other available finishes.

The following standard materials are used for the majority of Glenair backshells and connector accessories. However, backshell components are not limited to those items listed, but are representative of


the elements used in Glenair's general accessory products. Contact Glenair for applicable specifications on items not listed below.

STANDARD MATERIALS - BACKSHELLS AND ACCESSORIES

COMPONENT	MATERIAL	SPECIFICATION
Machined components: such as backshell bodies, fabricated elbows, protective covers, rotatable couplers, dummy stowage receptacles, lock nuts, G-spring support rings, EMI ground rings, grommet followers, etc.	Aluminum	AMS-QQ-A-200 ASTMB221, 209
Die cast components: such as angular backshells, strain relief backshells, strain relief bodies, strain relief saddles, special EMI ground rings, etc.	Aluminum	QQ-A-591 ASTMB85, 26
Backshells or strain reliefs: available in optional corrosion resisting steel; and hardware: such as screws, washers, rivets, wire rope, sash chain, band straps, etc.	Corrosion Resisting Steel	ASTMA582 (300 Series) AMS-QQ-S-763
Elastomeric seals: such as O-rings, cable jacket seals, grommets, etc.	Silicone	ZZ-R-765, MIL-R-25988
Anti-friction and thrust washers	Teflon	TFE
Anti-rotation device	Corrosion Resistant Material	N/A

BODY STRAP

Glenair offers an optional stainless steel body strap for attaching protective covers as illustrated. To specify body strap, add suffix letter C to the end of the part number. For example 360AS001M1610M6C.



2-56 Screw and Nut

NOTES

On all length callouts, tolerance is $\pm .060$ unless otherwise specified.

Unless otherwise specified, the following other dimensional tolerances will apply:

.xx = $\pm .03$ (0.8)
 .xxx = $\pm .015$ (0.4)
 Lengths = $\pm .060$ (1.52)
 Angles = $\pm 5^\circ$

Metric dimensions (mm) are indicated in parentheses

NOTE: For your convenience these tables have been reproduced inside the back cover fold-out.

Glenair Backshell and Accessory Material and Finish Options

Backshell and accessory base materials, plating options, specifications and codes

Code	Material	Finish	Finish Specification	Hrs. Salt Spray	Electrical Conductivity	Operating Temp. Range		Notes
A	Aluminum	Cadmium, No Chromate	SAE-AMS-QQ-P-416 Type I Class 3	48	Conductive	-65 to +175°C		Not recommended for new projects. LF is preferred.
AB	Marine Bronze	Unplated		1000	Conductive	-65 to +200°C	✓	Marine and geophysical applications.
AL	Aluminum	AlumiPlate, Clear Chromate	MIL-DTL-83488, Class 2, Type II over electroless nickel	1000	Conductive	-65 to +175°C	✓	Approved for MIL-DTL-38999L and MIL-DTL-83513G.
B	Aluminum	Cadmium, Olive Drab	SAE-AMS-QQ-P-416 Type II Class 3	96	Conductive	-65 to +175°C		Not recommended for new projects. NF is preferred.
C	Aluminum	Anodize, Black	AMS-A-8625 Type II Class 2	336	Non-Conductive	-65 to +175°C	✓	Glenair's standard black anodize finish.
E	Aluminum	Chem Film	MIL-DTL-5541 Type 1 Class 3	168	Conductive	-65 to +175°C		Glenair's standard chem film finish.
G	Aluminum	Anodize, Hardcoat	AMS-A-8625 Type III, Class 1, .001" thick	336	Non-Conductive	-65 to +200°C	✓	Glenair's preferred hardcoat finish.
J	Aluminum	Cadmium, Gold	SAE-AMS-QQ-P-416 Type II, Class 2 over electroless nickel	500	Conductive	-65 to +175°C		Not recommended for new projects. JF is preferred.
JF	Aluminum	Cadmium, Gold	SAE-AMS-QQ-P-416 Type II, Class 2 over electroless nickel	1000	Conductive	-65 to +175°C		Glenair's preferred gold cadmium finish.
LF	Aluminum	Cadmium, Clear	SAE-AMS-QQ-P-416 Type II Class 2 over electroless nickel	1000	Conductive	-65 to +175°C		Glenair's preferred clear cadmium finish.
M	Aluminum	Electroless Nickel	AMS-C-26074 Class 4 Grade B; ASTM-B-733, SC 2, Type IV	48	Conductive	-65 to +200°C	✓	Glenair's standard electroless nickel finish.
MT	Aluminum	Nickel-PTFE	GMF-002 Type II Class 1	1000	Conductive	-65 to +175°C	✓	Approved for MIL-DTL-38999L and MIL-DTL-83513G.
N	Aluminum	Cadmium, Olive Drab	SAE-AMS-QQ-P-416 Type II Class 3 over electroless nickel	500	Conductive	-65 to +175°C		Not recommended for new projects. NF is preferred.
NC	Aluminum	Zinc-Cobalt, Olive Drab	ASTM B 840 Grade 6 Type D over electroless nickel	350	Conductive	-65 to +175°C		Glenair's standard olive drab zinc-cobalt finish.
NF	Aluminum	Cadmium, Olive Drab	SAE-AMS-QQ-P-416 Type II Class 2 over electroless nickel	1000	Conductive	-65 to +175°C		Glenair's standard olive drab cadmium finish.
P	Stainless Steel	Electrodeposited Nickel	SAE-AMS-QQ-N-290 Class 1 Grade F	500	Conductive	-65 to +200°C	✓	Use ZM for electroless nickel alternative.
T	Aluminum	Cadmium, No Chromate	SAE-AMS-QQ-P-416 Type I Class 3	48	Conductive	-65 to +175°C		Not recommended for new projects. LF is preferred.
TP2	Titanium	Electrodeposited Nickel	SAE-AMS-QQ-N-290 Class 1 Grade F	96	Conductive	-65 to +200°C	✓	Glenair's preferred finish for titanium connectors.
U	Aluminum	Cadmium, Black	SAE-AMS-QQ-P-416 Type I Class 3	48	Conductive	-65 to +175°C		Not recommended for new projects. UF is preferred.
UC	Aluminum	Zinc-Cobalt, Black	ASTM B 840 Grade 6 Type D over electroless nickel	350	Conductive	-65 to +175°C		Glenair's standard black zinc-cobalt finish.
UCR	Aluminum	Zinc-Cobalt, Black	ASTM B 840 Grade 6 Type D over electroless nickel	350	Conductive	-65 to +175°C	✓	RoHS version of UC.
UF	Aluminum	Cadmium, Black	SAE-AMS-QQ-P-416 Type II Class 2 over electroless nickel	1000	Conductive	-65 to +175°C		Glenair's preferred black cadmium finish.
XAL	Composite	AlumiPlate	MIL-DTL-86448, Class 2, Type II over electroless nickel	2000	Conductive	-65 to +175°C	✓	Approved for MIL-DTL-38999L.
XB	Composite	Unplated Black		2000	Non-Conductive	-65 to +175°C	✓	Glenair's standard unplated composite.
XM	Composite	Electroless Nickel	AMS-C-26074	2000	Conductive	-65 to +175°C	✓	Glenair's standard electroless nickel finish over composite.
XMT	Composite	Nickel-PTFE	GMS-002 Class 2 Type II	2000	Conductive	-65 to +175°C	✓	Approved for MIL-DTL-38999L.
XO	Composite	Unplated Light Brown		2000	Non-Conductive	-65 to +175°C	✓	Not recommended for new projects. Use XB.
XW	Composite	Cadmium, Olive Drab	SAE-AMS-QQ-P-416 Type II Class 3 over electroless nickel	2000	Conductive	-65 to +175°C		Glenair's standard olive drab cadmium finish over composite.
XZN	Composite	Zinc-Nickel, Black	ASTM B841 Grade 5 over electroless nickel	2000	Conductive	-65 to +175°C		Glenair's standard black zinc-nickel finish over composite.
Z1	Stainless Steel	Passivate	SAE-AMS-SAE-AMS-QQ-P-35 Type VI	1000	Conductive	-65 to +200°C	✓	Glenair's standard passivated stainless steel.
Z2	Aluminum	Gold	MIL-DTL-45204 Class 1 over electroless nickel	48	Conductive	-65 to +200°C	✓	Glenair's standard gold plating for space programs.
ZC	Stainless Steel	Zinc-Cobalt, Black	ASTM-B840, Grade 6		Conductive	-65 to +175°C		Glenair's standard zinc-cobalt over stainless steel.
ZCR	Stainless Steel	Zinc-Cobalt, Black	ASTM-B840, Grade 6		Conductive	-65 to +175°C	✓	RoHS version of ZC.
ZL	Stainless Steel	Electrodeposited Nickel	SAE-AMS-QQ-N-290 Class 1 Grade F	1000	Conductive	-65 to +200°C	✓	Used on hermetic connectors. Use ZM for other applications.
ZM	Stainless Steel	Electroless Nickel	AMS-C-26074 Class 1 Grade A		Conductive	-65 to +200°C	✓	Glenair's preferred nickel-plated stainless steel.
ZMT	Stainless Steel	Nickel-PTFE	GMF-002 Type II Class 3	1000	Conductive	-65 to +175°C	✓	Glenair's new 1000 Hour Grey over stainless steel.
ZN	Aluminum	Zinc-Nickel, Olive Drab	ASTM B841 Grade 5 over electroless nickel	1000	Conductive	-65 to +175°C		Glenair's standard olive drab zinc-nickel finish.
ZNU	Aluminum	Zinc-Nickel, Black	ASTM B841 Grade 5 over electroless nickel	1000	Conductive	-65 to +175°C		Glenair's standard black zinc-nickel finish.
ZR	Aluminum	Zinc-Nickel, Black	ASTM B841 Grade 5 over electroless nickel	500	Conductive	-65 to +175°C	✓	Glenair's RoHs compliant black zinc-nickel.
ZU	Stainless Steel	Cadmium, Black	SAE-AMS-QQ-P-416 Type II Class 3	1000	Conductive	-65 to +175°C		Glenair's standard black cadmium over stainless steel.
ZW	Stainless Steel	Cadmium, Olive Drab	SAE-AMS-QQ-P-416 Type II Class 2 over electroless nickel	2000	Conductive	-65 to +175°C		Glenair's standard olive drab cadmium over stainless steel.