



SIGN	DATE	DESCRIPTION	APPROVER
△	12/22'07	Part NO.changed is from YK771xx1xx01G to YK771xx1xx00G.	kind
△	04/06'10	Screw changed is from YK771Screw to YK441Screw .	Aaron
△	04/23'10	Add is cULus	Aaron
△	05/05'11	It is changed to insert molding here.	Tason
△	09/22'11	The dimensional is changed from $\phi 0.11$ to $\phi 1.70$	Chen Bo
△	12/11'12	Update the drawing	Jacky

*THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!*

- MATERIALS ELECTRICAL**
- RATED VOLTAGE & CURRENT: 300V, 10 A
  - WITHSTAND VOLTAGE: AC 2000 V/Min
  - INSULATION RESISTANCE: 1000 M $\Omega$  OR MORE AT DC 500 V
  - OPERATING TEMPERATURE RANG: -40 °C ~ +115 °C
  - SCREW TORQUE VALUE: 12 lb-in
  - WIRE RANGE: 20- 14 AWG
  - APPROVAL:
  - Critical dimension:  $\nabla$

NO:	Name	Material/ standards	Number
①	Molded Parts:	Thermoplastic , UL 94 V-0	1
②	Molded Parts:	Thermoplastic , UL 94 V-0	1
③	Spring Clamp(L) :	Brass 0.8t	N
④	Spring Clamp(S) :	Brass 0.8t	N
⑤	Terminals:	Brass 0.8t	2xN
⑥	Terminals Screw:	Steel M3.5	2xN
⑦	Screw:	Steel M3.5x27.50 Zinc Plated	1
⑧	Screw:	Steel M3.5x17.20 Zinc Plated	1
⑨	Cushion:	Steel $\phi 5.7 \times 0.4$ t Ni Plated	2
⑩	Locking:	SK7 $\phi 4.7 \times 0.4$ t	2
⑪	BRASS NUT:	Brass M3.5	2
⑫	Cover:	PC 1.0t Transparent	1

**YK 771 xx 1 x x 00G** G: RoHS compliant (lead<4%) In copper Alloy MARK

NO. OF POLES: 04 2x2 POLES, 06 2x3 POLES, 08 2x4 POLES, ..... 30 2x15 POLES

Spring Clamps & SCREW PLATED 0: " @" MARK, 1: "ANY" MARK

△1 Contcat plated G/F & Screw plated Zinc  
 2 Screw plating G/F&contacts plating Sn  
 △3 Screw plating Zinc & contacts plating Sn(standard)

N=Number of 1/2poles

Dim A=(N-1)×9.525+16.8	→	Poles	Dim A Tol	Dim B Tol
Dim B=(N-1)×9.525		2×2P-2×5P	±0.30	±0.20
		2×6P-2×10P	±0.40	±0.30
		2×11P-2×15P	±0.50	±0.40

## ANYTEK

### CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		YK 77 SERIES (flange screw M3.5MM)		
PART NO.	YK771xx1xx00G	DWG NO.	8YK0002-77	
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.
			Jacky 2012.12.11	
				Tolerance
				X. ±0.50
				X.X ±0.30
				X.XX ±0.10
				X° ±1°

UNIT: mm, SCALE: NONE, SHEET: 01/01, REV.: F