


## NOTES

- 1 ONE EXAMPLE OF THE ROTATION OF REF. NO. ① TO REF. NO. ② IS SHOWN.
- 2 THE RECOMMENDED CLAMP TORQUE, REF. NO. ③: 3N·m.  
LOCTITE 242, HENKEL JAPAN OR EQUIVALENT IS RECOMMENDED TO PREVENT REF. NO. ④ FOR LOOSENING.
- 3 THE DIRECTION OF SOLDER CUP, REF. NO. ⑤ IS AN EXAMPLE.
- 4 THIS PRODUCTS TO BE USED WITH CABLE CLAMP, JR13WCC-\*(72).  
※ DESIGNATE DIAMETER(mm) OF APPLIED CABLE CABLE.

5	POLYACETAL	(WHITE)						
4	DIALYL PHTHALATE	(BLACK) UL94V-0		9	ZINC ALLOY	CROMATE PLATING		
3	DIALYL PHTHALATE	(BLACK) UL94V-0		8	SILICONE RUBBER	(BLACK)		
2	PHOSPHOR BRONZE	SILVER PLATING 3μm min.		7	BRASS	CROMATE PLATING		
1	ZINC ALLOY	CROMATE PLATING		6	SILICONE RUBBER	(RED)		
NO.	MATERIAL	FINISH, REMARKS		NO.	MATERIAL	FINISH, REMARKS		
UNITS mm		SCALE 2 : 1	COUNT 	DESCRIPTION OF REVISIONS		DESIGNED	CHECKED	DATE
 HIROSE ELECTRIC CO., LTD.	APPROVED : MO. SATOH		07.12.27	DRAWING NO.	EDC3-111149-71			
	CHECKED : YH. YAMADA		07.12.27	PART NO.	RM15WTPZ-3S(71)			
	DESIGNED : DS. MATSUNE		07.12.27	CODE NO.	CL109-1621-9-71			 1/1
	DRAWN : HN. TANAKA		07.12.14					