

SECTION A-A

N = Number of poles  
 Dim L =  $N \times 3.81 + 0.8$   
 Dim P =  $(N-1) \times 3.81$   
 Dim T =  $N \times 3.81 + 9.8$

	Dim L	Dim P	Dim T
2-6p	±0.15	±0.15	±0.15
7-12p	±0.20	±0.20	±0.20
13-18p	±0.30	±0.30	±0.30
19-24p	±0.40	±0.40	±0.40



SIGN	DATE	DESCRIPTION	APPROVER
△	6/23'06	Voltage/Current rating is changed from 160V/8A to 125V/4A	Marvin
△	6/23'06	Solid/Stranded wire is changed from AWG16-28 to AWG20-28	Marvin
△	6/23'06	Withstanding Voltage is changed from 1.3KV to 1.25KV	Marvin
△	12/02'08	Flange screw changed from "-" to "+/-"	Tony
△	11/21'09	The normal grey No. changed from RAL7004/P to RAL7035/D	Kind
△	02/22'11	Electrical is changed	Runner
△	05/10'11	The dimension is changed from 3.0 to 3.8	Runner
△	04/11'12	Contact is changed	Runner

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

#### Material

- Item ① Terminal body: Thermoplastic (UL94V-0)
- Item ② Terminal body: Thermoplastic (UL94V-0)
- Item ③ Terminal lever: Thermoplastic (UL94V-0)
- Item ④ Wire guard: Stainless Steel
- Item ⑤ Female contact: PhBz (CuSn) Tin plated
- Item ⑥ With flange screw: Steel M2.5 plated zinc "+/-"

#### Electrical

- Voltage rating: 300V △
- Current rating: 8A △
- Solid wire(AWG): 14-28 △
- Stranded wire(AWG): 14-28 △
- Wire strip length: 8-9mm
- Withstanding Voltage: 1.6KV △
- Operating temperature: -40°C to +115°C
- Safety Approval: 
- Critical dimension: 

#### PART NO.

HW xx 30 x 2 xxxx G

RoHS compliant (lead<4%) In copper Alloy

Poles  
 07 7 CONTACTS  
 08 8 CONTACTS  
 ...  
 24 24 CONTACTS


Color  
 0 Black  
 5 Green  
 (RAL 6018/T)  
 6 Blue  
 △ 8 Grey  
 (RAL 7035/D)

0000 Standard @ Logo  
 000A Standard ANY Logo  
 Any special item by customer request, please contact sales department.

# ANYTEK

## CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE	HW3.81 SERIES (with flange) 2P~24P				
PART NO.	HWxx30x2xxxxG		DWG NO.	8HW0102	
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	Tolerance
		Runner 2012.04.11	Tony 2008.12.02		X. ±0.50
				UNIT: mm	X.X ±0.30
				SCALE: NONE	X.XX ±0.10
				SHEET: 01/01	X° ±1°
				REV.: H	