

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

ALL RIGHTS RESERVED.

© COPYRIGHT — By —

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A1	REVISED PER ECR-19-017980	09DEC2021	SS	EW

11.4 [.449]

7.6 [.299]

6.6 [.260]

2.5 [.098]

2.3 [.091]

3.1 [.122]

5.3 [.209]

3.7 [.146]

2.8 [.110]

4.1 [.161]

SECTION A-A

SECTION B-B

SECTION C-C

1

2

3

4

5

6

7

8

NON DISPONIBILE DALL' AMP ITALIA
(NOT AVAILABLE FROM AMP ITALIA).

ADATTO PER AMP-O-MATOR
(REVERSE REELED FOR MINI APPLICATOR).

BOBINA IN CARTONE CON CARTA INTERPOSTA
QUANTITA' PER BOBINA: 3000
(CARTON REEL WITH INTERPOSED PAPER STRIP
Q.TY PER REEL: 3000).

CON SPECIALE RIVESTIMENTO IN CARTA
(WITH SPECIAL PAPER COVER).

BOBINA IN CARTONE CON CARTA INTERPOSTA
QUANTITA' PER BOBINA: 2500
(CARTON REEL WITH INTERPOSED PAPER STRIP
Q.TY PER REEL: 2500).

OBSOLETE.

BOBINA IN CARTONE
QUANTITA' PER BOBINA: 7000
(CARTON REEL
Q.TY PER REEL: 7000).

OBSOLETE PARTS: OBSOLETE CIS STREAMLINING
PER D.RENAUD/D.SINISI.

OBSOLETE	2	1	7	6	ST. (TIN PLTD)	BR. F. (PH. BR.)	4-280050-7	
	2	1	7		- (UNPLTD)	BR. F. (PH. BR.)	4-280050-4	
	2	1	7		ST. (TIN PLTD)	OTTONE (BRASS)	4-280050-2	
	2	1	7		- (UNPLTD)	OTTONE (BRASS)	4-280050-1	
	2	4			- (UNPLTD)	BR. F. (PH. BR.)	2-280050-4	
OBSOLETE	2	1	3		NICKELATO (NICKEL PLTD)	ACCIAIO (STEEL)	2-280050-3	
SUPERCEDED BY 1-280050-2	2	1	4	6	ST. (TIN PLTD)	OTTONE (BRASS)	2-280050-2	
OBSOLETE	2	1	4	3	- (UNPLTD)	OTTONE (BRASS)	2-280050-1	
	2	1			NICKELATO (NICKEL PLTD)	ACCIAIO (STEEL)	1-280050-3	
	2	5			ST. (TIN PLTD)	OTTONE (BRASS)	1-280050-2	
	2	1			ST. (TIN PLTD)	BR. F. (PH. BR.)	280050-7	
	2	1			- (UNPLTD)	BR. F. (PH. BR.)	280050-4	
	2	1			NICKELATO (NICKEL PLTD)	ACCIAIO (STEEL)	280050-3	
	2				ST. (TIN PLTD)	OTTONE (BRASS)	280050-2	
	2	1			- (UNPLTD)	OTTONE (BRASS)	280050-1	
					NOTE	FINITURA (FINISH)	MATERIALE (MATERIAL)	NUMERO (P/N)

DIAM. ISOLANTE
(INS. DIA. RANGE)
ø2.3-3.3

RANGO FILO
(WIRE RANGE)
0.5-1.5mm²

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN RAVI S 22NOV2016

CHK LI DAISY 22NOV2016

APVD DING TIM 22NOV2016

PRODUCT SPEC

APPLICATION SPEC

WEIGHT —

CUSTOMER DRAWING

DIMENSIONS:
mm [INCHES]

TOLERANCES UNLESS
OTHERWISE SPECIFIED:

0 PLC ± —
1 PLC ± 0.3 [.011]
2 PLC ± 0.40 [.015]
3 PLC ± —
4 PLC ± —
ANGLES ± 2°
FINISH

SEE TABLE

TE Connectivity

FASTON CONNECTOR .250 SR. FLAG REC. CONTACT

SIZE A3 CAGE CODE 00779 DRAWING NO C-280050

RESTRICTED TO —

SCALE NTS SHEET 1 OF 1 REV A1

1470-19 (1/15)