

Minimum wall thickness 1,5mm,
alternativ panel cut-out d=16,1

Technical specification:

Rated voltage: IEC 10107-2-101	4pos 250 V	5pos 60 V	8pos 30 V
Current rating: IEC 10107-2-101	4/5pos 4 A at 40°C	8pos 2 A at 40°C	
Insulation resistance: IEC 60512	≥100 MΩ		
Pollution degree: IEC 60664-1	3/2		
Degree of protection: IEC 60529	IP 67, in mated condition		
Temperature range:	-30°C ... +85°C		
Mating cycles: IEC 60512-9a	≥100		

Materials:

Contact:	CuZn
Contact plating:	Nickel, gold plated
Contact carrier:	PBT GF, UL 94
Sealing chassis:	NBR
Counternut:	CuZn, nickel plated
Socket housing:	CuZn, nickel plated
Grouting:	Polyurethane-resin, UL 94

Installation specification:


Recommended torque:	1-1,2 Nm
Conec installation tool:	Torque wrench: 36-000200 Insert across flats 19: 36-000250

Part no:	Description:	Pos	Length L:	D1	D2
43-01032	SAL - 12 - FSH4 - P5,5	4	5,5mm	Ø5,0	Ø1,6
43-01033	SAL - 12 - FSH5 - P5,5	5			
43-01034	SAL - 12 - FSH8 - P5,5	8			
43-01035	SAL - 12 - FSH4 - P12	4	12mm	Ø5,0	Ø1,6
43-01036	SAL - 12 - FSH5 - P12	5			
43-01037	SAL - 12 - FSH8 - P12	8			

DO NOT ALTER CAD DRAWING BY HAND

Directive 2011/65/EU RoHS compliant

Index: d 02.09.14 MG Ä5180
temperature range changed



dim. in mm

date

name

drawn

01.03.07

appd.

01.03.07

general tolerance:	0	± 0,50mm
	0,0	± 0,25mm
	0,00	± 0,10mm

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND
MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION.
OWNERSHIP AND COPYRIGHT OF CONEC GmbH



title:

Male socket M12x1 with dip solder,
backmounting

dwg no:

43K1A268

part no:

see table