







DimA=(N-1)×7.62+5.6
 DimB=(N-1)×7.62
 N=NUMBER OF CONTACTS

POLES	TOL
2p-6p	+0.20/-0.20
7p-12p	+0.30/-0.30
13p-16p	+0.40/-0.40

SIGN	DATE	DESCRIPTION	APPROVER
△	08/04'06	Current rating is changed from 10A to 20A	Marvin
△	08/04'06	Solid wire(AWG) standard is changed from 12-30 to 12-22	Marvin
△	08/04'06	Stranded wire(AWG) standard is changed from 12-30 to 12-22	Marvin
△	08/04'06	Torque standard is changed from 5 Lb-In to 4 Lb-In	Marvin
△	2010.03.31	Add the 2p mark	Jacke
△	2010.06.15	The design is changed	Cheng Bo
△	11/07'12	Update the drawing	Jacky

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material

- Item (a) Clamp: Brass(CuZn) Ni plated
- Item (b) Terminal screw: Steel Zinc plating "-" slot type
- Item (c) Female contact: PhBz ,Tin plated
- Item (d) Terminal (up body): Thermoplastic (UL94V-0)
- Item (e) Terminal (down body): Thermoplastic (UL94V-0)
- Item (f) Flange screw: Steel Zinc plating "+/-" slot type

Electrical cULus

- Voltage rating: 300VAC
- △ ● Current rating: 20A
- Wire range:
- △ ● Solid wire(AWG): 12-22
- △ ● Stranded wire(AWG): 12-22
- △ ● Torque: 4 Lb-In
- Screw: M3
- Wire strip length: 7-8mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -40°C to +115°C
- Safety Approval: 
- Critical dimension: 

EM xx 01 x 2 xxxx G

02 2 CONTACTS
 03 3 CONTACTS

 16 16 CONTACTS

Color
 0 Black (RAL9005)
 2 Red (RAL3001/D)
 3 Orange(RAL2011/P)
 4 Yellow(RAL1018/A)
 5 Green(RAL6018/T)
 6 Blue (RAL5015/A)
 8 Grey(RAL7035/D)

0000: "@" Logo
 000A: "ANYTEK" Mark
 Any special item by
 customer request,
 please contact sales
 department.


RoHS compliant
 (lead<4%) In
 copper Alloy

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		EM-7.62 Series With flange											
PART NO.	EMxx01x2xxxxG			DWG NO.	8EM0102								
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.									
			Jacky 2012.11.07		<table><tr><td>UNIT: mm</td><td>X. ±0.50</td></tr><tr><td>SCALE: NONE</td><td>X.X ±0.30</td></tr><tr><td>RFV: F</td><td>X.XX ±0.10</td></tr><tr><td></td><td>X° ±1°</td></tr></table>	UNIT: mm	X. ±0.50	SCALE: NONE	X.X ±0.30	RFV: F	X.XX ±0.10		X° ±1°
UNIT: mm	X. ±0.50												
SCALE: NONE	X.X ±0.30												
RFV: F	X.XX ±0.10												
	X° ±1°												
				SHFT: 01/01									



UNIT: mm
 SCALE: NONE

SHEET: 01/01

REV: F