



- Notes
- 1 The recommended crimp torque of ref.No. ⑤ shall be 0.15 to 0.2N·m.  
LOCTITE 263, HENKEL JAPAN or equivalent is recommended to prevent ref. No. ⑤ from loosening.
  - 2 Applicable cable :  $\phi 16 \pm 0.3$
  - 3 Assemble with applicable connector : RM31WTP-\*\*(71)  
\*\* shows number of contact, and male or female of connector.
  - 4 The cable pull and twisting strength(, waterproof tightness) and other characteristics may differ, depending on the cable structure, please confirm before the use.

3	Brass	Nickel plating			
2	Phosphor bronze	Nickel plating	5	Brass	Nickel plating
1	Brass	Nickel plating	4	Chloroprene rubber	(Black)
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS
<div> <div>UNITS mm</div> <div></div> <div>SCALE 2 : 1</div> <div>COUNT </div> <div>DESCRIPTION OF REVISIONS</div> <div>DESIGNED</div> <div>CHECKED</div> <div>DATE</div> </div>					
<b>HRS</b> HIROSE ELECTRIC CO., LTD.			APPROVED	HY. KOBAYASHI	16.01.25
			CHECKED	HY. KOBAYASHI	16.01.25
			DESIGNED	HY. KISHI	16.01.25
			DRAWN	HY. KISHI	16.01.25
			DRAWING NO.	EDC-110125-71-00	
			PART NO.	RM31WTP-CP(16)(71)	
			CODE NO.	CL109-1577-9-71	
					1/1