



- Notes
- ① The recommended tightening torque of ref.No. ① shall be 2 to 3N·m.
 - ② Across flats of hexagon hole of ref. No. ⑤ to be 1.27.
 - ③ The recommended tightening torque of ref.No. ⑤ shall be 0.2 to 0.3N·m.
One example of the rotation of ref. ⑤.
 - ④ The cable pull and twisting strength (, waterproof tightness) and other characteristics may differ, depending on the cable structure, please confirm before the use.

3	Synthetic rubber	(Black)			
2	Brass	Nickel plating	5	Stainless steel	JIS B 1177 Hexagon socket set screw M2.6×0.45×2
1	Brass	Nickel plating	4	Brass	Nickel plating JIS B 1111 Pan head machine screw M3×0.5×8
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS
UNITS mm		SCALE 2 : 1	COUNT 	DESCRIPTION OF REVISIONS	DESIGNED
					CHECKED
					DATE
HIROSE ELECTRIC CO., LTD.		APPROVED	HY. KOBAYASHI	16.01.05	DRAWING NO.
		CHECKED	HY. KOBAYASHI	16.01.05	PART NO.
		DESIGNED	HY. KISHI	15.12.26	CODE NO.
		DRAWN	HY. KISHI	15.12.26	
EDC-029119-71-00					1/1
RM21WTP-CP12<71>					
CL109-1477-4-71					