




- Notes
- 1 The recommended crimp torque of ref.No. ⑤ shall be 0.15 to 0.2N・m.
LOCTITE 263, HENKEL JAPAN or equivalent is recommended to prevent ref. No. ⑤ from loosening.
 - 2 Applicable cable : $\phi 14 \pm 0.3$
 - 3 Assemble with applicable connector : RM31WTP-**(71)
** shows number of contact, and male or female of connector.
 - 4 The cable pull and twisting strength(, waterproof tightness) and other characteristics may differ, depending on the cable structure, please confirm before the use.

3	Brass	Nickel plating											
2	Phosphor bronze	Nickel plating	5	Brass	Nickel plating								
1	Brass	Nickel plating	4	Chloroprene rubber	(Black)								
NO.	MATERIAL	FINISH . REMARKS		NO.	MATERIAL	FINISH . REMARKS							
UNITS mm			SCALE 2 : 1		COUNT	DESCRIPTION OF REVISIONS		DESIGNED		CHECKED		DATE	
 HIROSE ELECTRIC CO., LTD.		APPROVED		HY. KOBAYASHI		16.01.25		DRAWING NO.		EDC-110258-71-00			
		CHECKED		HY. KOBAYASHI		16.01.25		PART NO.		RM31WTP-CP(14)(71)			
		DESIGNED		HY. KISHI		16.01.25		CODE NO.		CL109-1579-4-71			
		DRAWN		HY. KISHI		16.01.25				