

f	0	0	0	0	0	0	0	0	0	0				0	0	0	0	0	0	0	0	0	0	0	0
e	E	E	E	E	E	E	E	E	E	E				E	E	E	E	E	E	E	E	E	E	E	E
d	E	E	E	E	E	E	E	E	E	E				E	E	E	E	E	E	E	E	E	E	E	E
c	E	E	E	E	E	E	E	E	E	E				E	E	E	E	E	E	E	E	E	E	E	E
b	E	E	E	E	E	E	E	E	E	E				E	E	E	E	E	E	E	E	E	E	E	E
a	E	E	E	E	E	E	E	E	E	E				E	E	E	E	E	E	E	E	E	E	E	E
z	0	0	0	0	0	0	0	0	0	0				0	0	0	0	0	0	0	0	0	0	0	0
P	0	0				1				1				2				2							
O	1	5				0				5				0				5							
S																									

Diagram E shows a side view of a medical device. The device has a total length of 24.20 units. The distance from the left end to the center of the connector is 9.70 units. The distance from the center of the connector to the right end is 14.50 units. A vertical line marks the 'SEATING PLANE FOR CONNECTOR' at the center of the connector.

Technical drawing of a reinforced concrete slab cross-section. The slab is 8.00 units thick and contains two layers of reinforcement. The top layer has 10 bars, and the bottom layer has 10 bars. The spacing between bars is 2.00 units. The total width of the slab is 20.00 units. The drawing shows the reinforcement layout and dimensions.

NOTES PLATING CODE (DIGIT 13 AND 14)  
(REF DRW NO. BS,C , 201844 , 003)

1. THIS PRODUCT IS CSA APPROVED.
2. THIS PRODUCT IS UL RECOGNIZED.
3. MEASURED AT THE BOTTOM.
4. MATERIAL CONTACT: PHOSPHORBRONZE  
HOUSING: CREAM WHITE GLASS FILLED POLYESTER UL-94V0
5. CONNECTOR PRINTED WITH P/N AND DATE CODE.
6. FOR ACTUAL CONTACT LOADINGS, SEE LOADING PATTERN MATING SIDE.
7. SHAPE OF CONNECTOR HOUSING CAN ALTER DEPENDING ON  
PRODUCTION LOCATION
8. THE PRODUCT (LF) MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY  
REGULATIONS AS DESCRIBED IN GS-22-008
9. FOR RECOMMENDED PTH DIMENSIONS REFER DRAWING : BS, A , 201572 , 001

CATALOG NO: HM2P07PME120----

[illegible]