



Notes

- 1 Rotation examples of ref. No. ⑧ to ref. No. ① is shown.
- 2 The recommended clamp torque of ref. No. ⑧ : 3 N·m.
LOCTITE 243, HENKEL JAPAN or equivalent is recommended to prevent ref. No. ⑧ from loosening.
- 3 This products to be used with cableclamp : JR16WCC-*(72).
* designate diameter of applicable cable.
- 4 The cable pull and twisting strength, waterproof tightness and other characteristics may differ.
depending on the cable structure.
Please confirm before the use.

NO.	MATERIAL	FINISH .	REMARKS	NO.	MATERIAL	FINISH .	REMARKS
4	PPS	(BLACK)	UL94V-0	8	ZINC ALLOY	CHROME PLATING	
3	PPS	(BLACK)	UL94V-0	7	BRASS	CHROME PLATING	
2	COPPER ALLOY	SILVER PLATING 2 μm min.		6	SILICONE RUBBER	(BLACK)	
1	BRASS	CHROME PLATING		5	POLYACETAL	(WHITE)	
UNITS mm				SCALE 2 : 1		COUNT 1	DESCRIPTION OF REVISIONS DIS-C-00000841
							DESIGNED KN. IKEHARA
							CHECKED HY. KOBAYASHI
							DATE 16.03.02
				APPROVED : HY. KOBAYASHI 15.11.06		DRAWING NO.	EDC-115324-81-00
				CHECKED : HY. KOBAYASHI 15.11.06		PART NO.	RM15WTJZA-4S(81)
				DESIGNED : KN. IKEHARA 15.11.06		CODE NO.	CL109-1905-6-81
				DRAWN : KN. IKEHARA 15.11.06			

HRS HIROSE ELECTRIC CO., LTD.