

Notes ①. The contact will be sent with Ref. No. ④ press-fitted to Ref. No. ③.

2. Rotation examples of ref no. ① and ② are shown

① 3. Recommended Crimping Tool: JIS-C-9711 IZUMI CO., LTD REC-Li150


4. Make sure that the Keigland shell is tightened to the end of the screw. The recommended tightening torque is 3N·m. Furthermore, to prevent loosening, it is recommended that thread-locking fluid be used.

5. This product is **III** certified. (File E481344)

6. Deformities and the like may occur, so when mated

Please do not leave with the mating guide of the opposite side and the arrow marks out of alignment

WARNING: This product is not hot pluggable.

3	Copper	Silver plating	3 μ m			
2	PBT	(Black)	UL94V-0	5	PBT	(Black) UL94V-0
1	PBT	(Black)	UL94V-0	4	PBT	(Black) UL94V-0
NO.	MATERIAL	FINISH	REMARKS	NO.	MATERIAL	FINISH
UNITS mm	SCALE 1 : 1	COUNT 1	DESCRIPTION OF REVISIONS DIS-C-00002363	DESIGNED TP. KOMATSU	CHECKED YH. YAMADA	DATE 18.08.03
 HIROSE ELECTRIC CO., LTD.	APPROVED : EJ. KUNII		16.08.08	DRAWING NO.	EDC-119510-00-00	
	CHECKED : EJ. KUNII		16.08.08	PART NO.	EM30M-BP-1PCA-K	
	DESIGNED : TY. TAKAHASHI		16.08.08	CODE NO.	CL138-0076-0-00	1
	DRAWN : TY. TAKAHASHI		16.08.08			