


REV.	ECN NO.	DATE	SIGN	DESCRIPTION
B	C201347	2020-09-03	Eric	$\triangle B$ X2
C	C201590	2020-10-19	Allen Pan	$\triangle C$ x1
D	C201758	2020/12/07	Allen	$\triangle D$ x5.



Note:  $\triangle D$

- \*  $\text{CC}$  Important Dimension
- \* Shell: Metal.
- \* Nut: Metal.
- \* Panel O-Ring: Rubber, Gray.
- \* Mating O-Ring: Rubber, Red.
- \* For Panel Thickness Max 4mm.
- \* Recommended Nut Torque: 4-6kgf.cm.
- \* Assemble Gasket and Nut on Connector.

UNIT:mm			TITLE $\triangle C$ MI2 SMT Female Front Fastened Hexagonal Nut Package
TOLERANCE .X $\pm 0.25$ .XX $\pm 0.1$ .XXX $\pm 0.05$ ANGLES $\pm 1^\circ$	SCALE 2:1	SIZE A4	SHEET 1 OF 1
	REV. D	WC-REV. A.1	$\text{CC}$ : Inspection item

ITEM NO APPM-AAFA012-001	DRAWN BY Allen Pan	DATE 2020-06-16
DWG NO APPM-AAFA012-001	CHECKED BY Sam Ho	DATE 2020-06-16
CUSTOMER ALTW	APPROVED BY Fred Lee	DATE 2020-06-16

Amphenol LTW  
安費諾亮泰企業股份有限公司

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.