






2198232
FINISHED ASSEMBLY
SCALE 4:1

- 1 MATERIAL:
CAGE ASSEMBLY: 0.25mm THICK NICKEL SILVER ALLOY
EMI SPRINGS: COPPER ALLOY
HEAT SINK: ALUMINUM
HEAT SINK/LIGHTPIPE CLIP: STAINLESS STEEL.
LIGHTPIPE: POLYCARBONATE, CLEAR
- 2 FINISH:
SPRINGS: MINIMUM OF 0.8um TIN PLATE OVER MINIMUM OF 0.8um NICKEL UNDERPLATE. NON-PLATED EDGES PERMISSIBLE.
HEAT SINK: ELECTROLESS NICKEL
HEAT SINK CLIP: PASSIVATE.
- 3 DATUM AND BASIC DIMENSIONS ESTABLISHED BY CUSTOMER.
- 5 PADS AND VIAS CHASSIS GROUND.
5. MATES WITH SFP MSA COMPLIANT RECIEVERS.
6. INTERPRETATION OF DATUM REFERENCE FRAME IN ACCORDANCE WITH SECT 4.4.1.1 OR ASME Y14.5M-1994.
- 7 MINIMUM PC BOARD THICKNESS:
SINGLE SIDED: 1.5mm
DOUBLE SIDED: 2.25mm
- 8 HOLE PATTERN REPEATS FOR EACH PORT, SPACING BETWEEN PORTS IS 14.25mm.
- 9 REFERENCE APPLICATION SPEC. 114-13120, HOLE A, FOR RECOMMENDED DRILL HOLE DIAMETER AND PLATING THICKNESS.

LOC	DIST	REVISIONS					
GP	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
			A	RELEASED PER ECO-12-013192	08OCT2012	BMM	MRS
			A1	RELEASED PER ECO-14-008488	06JUNE2014	PP	SH


- 10 REFERENCE APPLICATION SPEC. 114-13120, HOLE B, FOR RECOMMENDED DRILL HOLE DIAMETER AND PLATING THICKNESS.
11. CERTAIN MATING TRANCEIVERS MAY REQUIRE ADDITIONAL PCB THICKNESS THAT WOULD NEED TO BE DETERMINED BY THE CUSTOMER.
12. PRODUCT COMPLIES WITH SPECIFICATION SFF-8433 IMPROVED PLUGGABLE FORM FACTOR FOR SFP+ GANGED CAGES.
- 13 DIMENSION APPLIES PRIOR TO INSERTION OF SFP MODULE.
- 14 HEATSINK, HEATSINK CLIP, AND LIGHTPIPE SHIPPED UNASSEMBLED TO CAGE ASSEMBLY. CAGE ASSEMBLY TO BE PRESSED INTO PCB PRIOR TO ATTACHING HEATSINK, HEATSINK CLIP, AND LIGHTPIPE TO THE CAGE ASSEMBLY.
- 15 PACKAGED AS A COMPLETE ASSEMBLY.




13	22.5	NETWORKING, TALL	2198232-4
13	18.1	NETWORKING, SHORT	2198232-3
14	15.5	SAN	2198232-2
14	13.2	PCI	2198232-1
A MAX		DESCRIPTION	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN B. MATTHEWS 01NOV2011	TE Connectivity	
		CHK M. SCHMITT 01NOV2011		
DIMENSIONS:		APVD W. SCHMITT 01NOV2011	NAME	
mm		PRODUCT SPEC	SFP+ ENHANCED 1X2 CAGE ASSEMBLY, PRESS-FIT, EXTERNAL EMI SPRINGS, WITH HEATSINK AND LIGHTPIPE	
		108-2364	SIZE	
		APPLICATION SPEC	CAGE CODE DRAWING NO	
		114-13120	RESTRICTED TO	
MATERIAL		WEIGHT	A100779C=2198232	
		Customer Drawing	SCALE 5:1 SHEET 1 OF 4 REV A1	


LOC		DIST		REVISIONS					
GP	00	P	LTR	DESCRIPTION			DATE	DWN	APVD
		-		SEE SHEET 1			-	-	-




RECOMMENDED BEZEL CUT-OUT
SINGLE SIDED APPLICATIONS
SCALE 4:1



RECOMMENDED BEZEL CUT-OUT
BELLY TO BELLY APPLICATIONS



2198232
MOUNTED ON PC BOARD
SHOWN THRU RECOMMENDED BEZEL



2198232
MOUNTED BELLY TO BELLY ON PC BOARD
SHOWN THRU RECOMMENDED BEZEL

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN B. MATTHEWS	01NOV2011	TE Connectivity	
		CHK M. SCHMITT	01NOV2011		
DIMENSIONS:		APVD M. SCHMITT	01NOV2011	NAME	
mm		PRODUCT SPEC		SFP+ ENHANCED 1X2 CAGE ASSEMBLY, PRESS-FIT, EXTERNAL EMI SPRINGS, WITH HEATSINK AND LIGHTPIPE	
		108-2364		SIZE	
		APPLICATION SPEC		CAGE CODE	
		114-13120		DRAWING NO	
		WEIGHT		RESTRICTED TO	
		Customer Drawing		A100779	
				SCALE	
				5:1	
				SHEET	
				2	
				OF	
				4	
				REV	
				A1	

