

SUMMARY

Wires

Low voltage 5



Image is for illustrative purpose only

Series	2P
Termination type	Male crimp
IP rating	66
AWG wire size	28.00 - 20.00
Cable Ø	5.30 - 7.20 mm
Status	active
Matching parts	CNB.M05.GYMG

Download

[Request a quote](#)

[Catalog](#)

TECHNICAL DETAILS

Mechanics

Shell Style/Model	CF*: Straight plug with cable collet, watertight (IP 66) and nut for fitting a bend relief
Keying	3 keys (alpha=0, gamma=60; Plug: male contacts; Receptacle: female contacts)
Housing Material	PSU (Polysulfone), gray
Weight	10.04 g

Performance

Configuration	2P.M05 : 5 Low V.
Insulator	Y: PEEK for crimp contacts
Rated Current	14 Amps

Specifications

Test voltage (kV rms) Contact-contact: 1.75
Air clearance min.: 1.75 mm
Creepage distance min.: 1.75 mm

Others




Endurance (Shell): >1000 mating cycles
Temp (min / max): -50°C / +150°C
F ret (min): 150 N

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

F ret (max): 250 N

Steam sterilization: 20 times (with potting on rear connection)

DRAWINGS



RECOMMENDED BY LEMO

Tools

Crimp Tool: [DPC.91.701.V](#)

Crimp settings: AWG/Selector = 18-20/8-7

Positionner: [DCE.91.132.BVC](#)

Replacement contact: FGG.2B.565.ZZC

Cables

CMN.05.T18.065PGZE		Grey	
CMN.05.T18.065PNZE			

CMN.05.T20.057PGZE		Grey	
CMN.05.T20.057PNZE			
CMN.05.T20.057QGZE	TPR (medical)	Grey	
150250	PVC	Grey	
250500	PVC	Grey	

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.