

RF Attenuator
6920.02.A

Description

Standard Attenuator, Low Power



Product Configuration

Connector (side 1 / side 2)	BNC plug (male) / BNC jack (female)
Interface Standards	IEC 60169-8_MIL-STD-348A/301_CECC 22120

Technical Data

Electrical Data			
Nominal impedance	75 Ω		
Nominal attenuation	20 dB		
Frequency range	DC to 1 GHz		
Frequency sub range (GHz)	DC to 0.5	0.5 to 0.7	0.7 to 1
Attenuation deviation (±dB)	0.5	0.5	0.8
VSWR max.	1.1	1.2	1.2
Power rating	0.4 Watt average power up to 30 °C ambient temperature, linearly derated to 0 Watt at 130 °C ambient temperature. 500 Watt peak power, 5 µs pulse, 0.05 % duty cycle		

Mechanical Data

Weight	0.025 kg
--------	----------

Environmental Data

Operating temperature	-55 °C to 130 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Material Data

Piece Part (side 1)	Material	Surface Plating
Centre contact	Brass	Gold Plating
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Piece Part (side2)	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	

Related Documents

Outline drawing	DOU-00005308
-----------------	--------------

Ordering Information

Single packaging	6920.02.A
------------------	-----------