

Note: This datasheet may be out of date Please download the latest datasheet of VFR3VD31E131U31# from the official website of Murata Manufacturing

### VFR3VD31E131U31#

"#" indicates a package specification code.








< List of part numbers with package codes > VFR3VD31E131U31A




## Appearance & Shape



# Packaging Information





Packaging	Specifications	Minimum Order Quantity
А	Ammo Pack	2000



Other Usage

For general

1 of 4

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.



Note: This datasheet may be out of date.

Please download the latest datasheet of VFR3VD31E131U31# from the official website of Murata Manufacturing Co.. Ltd.

http://www.murata.com/en/products/productdetail?partno=VFR3VD31E131U31%2

### VFR3VD31E131U31#

"#" indicates a package specification code.



VFR3V series is designed for ESD surge protection of IC. It efficiently absorbs ESD surges rushed into IC's I/O terminal.

#### **Applications**

Elimination of noise and protection of semiconductors in office equipment, including computers and peripheral equipment, copy machines, and communication terminals.

2 of 4

### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.






Note: This datasheet may be out of date Please download the latest datasheet of VFR3VD31E131U31# from the official website of Murata Manufacturing Co., Ltd.

## VFR3VD31E131U31#

"#" indicates a package specification code.



Shape	Lead
Length	8.0mm
Length Tolerance	max.
Width	2.3mm
Width Tolerance	max.
Thickness	5.0mm
Thickness Tolerance	max.
Rated Current	20mA
Operating Temperature Range	-25°C to 85°C
Mass(typ.)	0.23g
Rated Voltage	25Vdc
Varistor Voltage	50Vdc
Varistor Voltage Torelance	±20%
Capacitance	130pF
Capacitance Tolerance	±20%
Peak Pulse Current	30A
ESD Test	15kV,100times

3 of 4

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.




Note: This datasheet may be out of date

Please download the latest datasheet of VFR3VD31E131U31# from the official website of Murata Manufacturing Co., Ltd.

## VFR3VD31E131U31#

"#" indicates a package specification code.





Insertion Loss Characteristics

4 of 4

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

