






THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

REV.	ECN NO.	DATE	SIGN	DESCRIPTION



Pin Assignment
Front View



Recommended
Panel Cut-Out

- Note:
- * $\varnothing$ Important Dimension.
 - * Waterproof Rate: IP67.
 - * Housing: Nylon+GF, Black.
 - * Male Pin: Copper Alloy, Gold Plated.
 - * Screw Nut: Nylon+GF, Black.
 - * O-Ring: EPDM, Black.
 - * For Panel Thickness Max 3.0mm.

UNIT:mm		TITLE M8 2Pin Panel M Conn. M Pin		ITEM NO 8AP-02PMMS-SF7001		DRAWN BY Mila		DATE 2014-01-08	
TOLERANCE .X ±0.25 .XX ±0.1 .XXX ±0.05 ANGLES ±1°		SCALE 3:1	SIZE A4	SHEET 1 OF 1	DWG NO 8AP-02PMMS-SF7001	CHECKED BY Jimmy		DATE 2014-01-08	
REV. A		WC-REV. A.5	$\varnothing$: Inspection item		CUSTOMER ALTW	APPROVED BY Jerry		DATE 2014-01-08	

Amphenol LTW
安費諾亮泰企業股份有限公司