


HBT 6,0 - 3,0 GE**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



The use of insulated connectors guarantees users a permanent and consistent quality for their electrical connections.

In addition, they bring advantages during installation.

General ordering data

Version	cable lug, terminal end, Insulated cable connector, 4 mm ² - 6 mm ² , yellow
Order No.	1312470000
Type	HBT 6,0 - 3,0 GE
GTIN (EAN)	4050118114980
Qty.	100 pc(s).

HBT 6,0 - 3,0 GE**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Net weight	1.58 g
------------	--------

Technical data

Description of article	isolated hook-blade cable lug
------------------------	-------------------------------

Connectors

Conductor cross-section, max.	6 mm ²	Conductor cross-section, min.	4 mm ²
Identification colour	yellow	Insulation	Available
Material/plastic	PC		

Dimensions

Hook nose X	2.8 mm	Insulation cross-section	6.4
Length L	30.2 mm	Pin length P	17.2 mm
Pin width B	3 mm		

Classifications

ETIM 6.0	EC001059	ETIM 7.0	EC001059
ETIM 8.0	EC001059	ECLASS 9.0	27-40-02-92
ECLASS 9.1	27-40-02-12	ECLASS 10.0	27-40-02-92
ECLASS 11.0	27-40-02-92	ECLASS 12.0	27-40-02-92

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	EPLAN
Catalogues	Catalogues in PDF-format
Brochures	