

Item number: S23L0C-P08PPL0-120S



ODU MINI-SNAP® connector

8-pin

connector - protection class IP 50 with clamping nut for bend protection*

*Please order protective grommets separately

Housing: matt chrome-plated

(Example: image representation of the design)

Dimensions



Number of poles: 8 poles



contact insert

8-pin
pin (single contacts)
Crimp clip contact

Coding 0 °



Insulation material:	PEEK
Contact diameter:	0
Cable diameter:	from 10 mm to 10 mm
Max. Connection cross section:	AWG 18/20 / 0.50 / 1.00
	2 mm
Connection	diameter : 0 mm

Technical specifications

Continuity resistance :	kA μΩ
Insulation resistance:	10 ^ 16 Ω
Air and creepage distance:	0 mm according to IEC 60664-1: 2007 (VDE 0110-1: 2008)
Current load Single contact:	0 A
Current load compl. Application:	0 A VDE 0298-4: 2013
Test voltage:	0 kV
SAE AS 13441: 2004 method 3001.1	
Rated voltage:	0 kV SAE AS 13441: 2004 method 3001.1

All dimensions in mm. All illustrations are illustrations. Subject to change.

General information about ODU MINI-SNAP Application

temperature: -40 ° C to + 120 ° C