


SMD Power Inductor C252012/DS




sumida

Under Development




**Halogen
Free**




Description

- Multilayer power inductor.
- Magnetically shielded.
- L × W × H: 2.65 × 2.15 × 1.2 mm Max.
- Product weight: 28mg (Ref.)
- Moisture Sensitivity Level: 1
- RoHS compliance.
- Halogen Free available.

Dimension - [mm]



Land pattern and Schematics - [mm]



Electrical Characteristics

Part No.	L(μH) ±20% ※1	D.C.R. (mΩ) ±25%	Saturation current (mA) ※2	Temperature rise Current (mA)※3
C252012WB-R47	0.47	50	2300	2300
C252012WB-1R0	1.0	80	2000	1900
C252012WB-1R5	1.5	105	1600	1700
C252012WB-2R2	2.2	130	1500	1400
C252012WB-3R3	3.3	230	1300	1000
C252012WB-4R7	4.7	320	1200	900

※1. Inductance measuring condition: at 3MHz.

※2. Saturation current: The value of D.C. current when the inductance decreases to 70% of it's nominal value.

※3. Temperature rise current: The value of D.C. current when the temperature rise is Δt=40°C (Ta=25°C).






SMD Power Inductor C252012/DS



Under Development

Saturation Current & Temperature Rise Graph

— L (20°C) — ΔT





SMD Power Inductor C252012/DS



 **sumida**

Under Development

Solder Reflow Condition



Please refer to the sales offices on our website - <http://www.sumida.com>

Hong Kong

Tel. +852-2880-6688
FAX. +852-2565-9600
sales@hk.sumida.com

Tokyo

Tel. +81-3-5202-7112
FAX. +81-3-5202-7105
sales@jp.sumida.com

Chicago

Tel. +1-847-545-6700
FAX. +1-847-545-6720
sales@us.sumida.com

Shanghai

Tel. +86-021-5836-3299
FAX. +86-021-5836-3266
shanghai.sales@cn.sumida.com

Seoul

Tel. +82-2-6237-0777
FAX. +82-2-6237-0778
sales@kr.sumida.com

Obernzell

Tel. +49-8591-937-0
FAX. +49-8591-937-103
contact@sumida-eu.com

Shenzhen

Tel. +86-755-8291-0228
FAX. +86-755-8291-0338
shenzhen.sales@cn.sumida.com

Singapore

Tel. +65-6296-3388
FAX. +65-6296-3390
sales@sg.sumida.com

Neumarkt

Tel. +49-9181-4509-110
FAX. +49-9181-4509-310
infocomp@eu.sumida.com

Taipei

Tel. +886-2-8751-2737
FAX. +886-2-8751-2738
sales@tw.sumida.com

San Jose

Tel. +1-408-321-9660
FAX. +1-408-321-9308
sales@us.sumida.com