

承認書

SPECIFICATION FOR APPROVAL

CUSTOMER: _____


DESCRIPTION: _____ WIRE WOUND CHIP INDUCTOR

DDY PART NO: _____ WI0805LD470KST-HF

CUSTOMER MODEL NO: _____

DRAWING		
MADE	CHECKED	APPROVED
譚晶晶	黃志偉	肖中華
DATE:	2024年4月12日	

CUSTOMER APPROVE



惠州市德立电子有限公司
HUI ZHOU DE LI ELECTRONICS CO., LTD

廣東省博羅縣洲際工業園梅園三路

NO.3 MEI YUAN ROAD,ZHOU JI INDUSTRIAL AREA,BOLUO COUNTY GUANGDONG

電話: 15970768093 13640935893

傳真: 0752-6207969

郵編: 516100

[Http://ddycoils.com](http://ddycoils.com)



惠 州 市 德 立 电 子 有 限 公 司
HUI ZHOU DE LI ELECTRONICS CO., LTD

CUSTOMER:		REV NO:	A
DESCRIPTION:	WIRE WOUND CHIP INDUCTOR	PAGE NO:	PAGE 1 OF 6
PART NO:	WI0805LD-C系列	SN.	
CUSTOMER NO:		DATE:	2024年4月12日

CATALOG

Resume		P2
Shape & Dimension		P3
Part numbering ststem		P3
General specification		P3
Electrical Characteristics List		P4
Soldering Conditions		P5
Package Information		P6






惠州市德立电子有限公司
HUI ZHOU DE LI ELECTRONICS CO., LTD

CUSTOMER:		REV NO:	A
DESCRIPTION:	WIRE WOUND CHIP INDUCTOR	PAGE NO:	PAGE 3 OF 6
PART NO:	WI0805LD-C系列	SN.	
CUSTOMER NO:		DATE:	2024年4月12日

1.SHAPE & DIMENSION



CODE		L(MAX)	W(MAX)	T(MAX)	E(Typ.)	F(Typ.)	D(Typ.)
DIMENSION	WI0805LD	2.40	1.73	1.52	1.02	1.78	0.76

2. PART NUMBERING SYSTEM

WI	0805	LD	220	K	S	T	-	C	-	HF
1	2	3	4	5	6	7		8		9
1 PRODUCT SYMBOL (产品代号)										
2 DIMENSIONS (规格尺寸)										
3 MATERIAL (芯片类型)										
4 INDUCTANCE (电感量)										
5 TOLERANCE (公差) : J±5%; K±10%; M±20%										
6 TERMINAL (端电极材料) : S-锡端头										
7 PACKAGING (包装方式) : T-编带盘装; B-散装										
8 Color (颜色) : C-点色										
9 E.P. (环保) : LF—Lead Free HF—Halogen Free FP—Red Phosphor Free										

3.GENERAL SPECIFICATION

- a. Rating DC current: Temperature rise(ΔT) is 40℃ approximately at Irms.
- b.Operating temp.: -40℃~+85℃(Including self-generated heat).
- c.Storage temp.: -10℃ ~+40℃ R.H.: 65% Max
- d.Moisture sensitivity level (MSL) 2 (1 year floor life at <30℃/65% relative humidity)

APPROVED BY	CHECKED BY	DRAFT
肖中华	黄志伟	谭晶晶



惠 州 市 德 立 电 子 有 限 公 司

HUI ZHOU DE LI ELECTRONICS CO., LTD

CUSTOMER:						REV NO:	A		
DESCRIPTION:	WIRE WOUND CHIP INDUCTOR					PAGE NO:	PAGE 4 OF 6		
PART NO:	WI0805LD-C系列					SN.			
CUSTOMER NO:						DATE:	2024年4月12日		
4. Electrical Characteristics List									
NO.	Part Number	L	Freq	Q	SRF	Rdc	Irms	产品公差	Color
		(μH)	(MHz)	(Typ)	(MHz)Typ	(Ω)max	(mA)Typ		
1	WI0805LDR68□ST-C-HF	0.68	7.9	14	765	0.19	1200	K,M	灰
2	WI0805LD1R0□ST-HF	1	7.9	14	208	0.17	1100	K,M	\
3	WI0805LD1R2□ST-C-HF	1.2	7.9	14	208	0.17	960	K,M	红
4	WI0805LD1R5□ST-C-HF	1.5	7.9	14	130	0.22	880	K,M	棕
5	WI0805LD1R8□ST-C-HF	1.8	7.9	14	112	0.26	860	K,M	橙
6	WI0805LD2R2□ST-C-HF	2.2	7.9	12	80	0.31	740	K,M	红
7	WI0805LD3R3□ST-C-HF	3.3	7.9	12	50	0.36	620	K,M	橙
8	WI0805LD4R7□ST-C-HF	4.7	7.9	14	51	0.56	520	K,M	黄
9	WI0805LD5R6□ST-C-HF	5.6	7.9	12	42	0.65	480	K,M	蓝
10	WI0805LD6R8□ST-C-HF	6.8	7.9	14	35	0.88	420	K,M	绿
11	WI0805LD8R2□ST-C-HF	8.2	7.9	13	33	0.94	400	K,M	紫
12	WI0805LD100□ST-C-HF	10	2.5	14	25	1.17	300	J,K,M	蓝
13	WI0805LD120□ST-C-HF	12	2.5	14	30	1.50	290	J,K,M	灰
14	WI0805LD150□ST-C-HF	15	2.5	15	28	1.82	280	J,K,M	紫
15	WI0805LD180□ST-C-HF	18	2.5	15	27	2.01	260	J,K,M	白
16	WI0805LD220□ST-C-HF	22	2.5	15	20	2.29	240	J,K,M	灰
17	WI0805LD470□ST-HF	47	2.5	14	15	4.42	160	J,K,M	\
18	WI0805LD560□ST-C-HF	56	2.5	14	10	5.75	150	J,K,M	黄
19	WI0805LD680□ST-C-HF	68	2.5	14	10	5.90	140	J,K,M	棕
20	WI0805LD820□ST-C-HF	82	2.5	14	10	9.75	100	J,K,M	橙
21	WI0805LD101□ST-C-HF	100	1.0	10	5	9.75	100	J,K,M	红
产品公差：K±10%；M±20%									
APPROVED BY			CHECKED BY			DRAFT			
肖中华			黄志伟			谭晶晶			




惠州市德立电子有限公司
HUI ZHOU DE LI ELECTRONICS CO., LTD

CUSTOMER:		REV NO:	A
DESCRIPTION:	WIRE WOUND CHIP INDUCTOR	PAGE NO:	PAGE 5 OF 6
PART NO:	WI0805LD-C系列	SN.	
CUSTOMER NO:		DATE:	2024年4月12日

5. SOLDERING CONDITIONS


Figure 1.
Re-flow
Soldering
(Lead Free)



Note:

- Preheat circuit and products to 150°C
- 260°C tip temperature (max)
- Reflow times: no more than 2 times
- Solder paste thickness: the best 0.08mm is ,but max is 0.1mm

Figure 2.
Hand
Soldering



Note:

- Use a 20 watt soldering iron with tip diameter of 1.0mm
- Limit soldering time to 3 sec.


APPROVED BY	CHECKED BY	DRAFT
肖中华	黄志伟	谭晶晶




惠州市德立电子有限公司
HUI ZHOU DE LI ELECTRONICS CO., LTD

CUSTOMER:		REV NO:	A
DESCRIPTION:	WIRE WOUND CHIP INDUCTOR	PAGE NO:	PAGE 6 OF 6
PART NO:	WI0805LD-C系列	SN.	
CUSTOMER NO:		DATE:	2024年4月12日


6. PACKAGING(unit: mm)



胶带 POLYSTYRENE TAPE



Peeling off force
Pull strength
0402~1210:20g~80g
Speed of peeling off:
300mm/min±10%



胶带		A	B	T
	0805	1.85	2.4	1.45

Type	ΦA	ΦB	ΦC	ΦD	E	W	t	
0805	178	60	13	21	2	8.4	2	

包装数量(PACKAGING QUANTITY): 2000Pcs/盘

注意:

此物料不涉及汽车或相关产品方面的应用, 否则, 由此引起的一切品质和责任问题, 我司将概不承担。

APPROVED BY	CHECKED BY	DRAFT
肖中华	黄志伟	谭晶晶