

1156781

https://www.phoenixcontact.com/us/products/1156781

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



DIN rail connector, color: light gray, nominal current: 6 A, 4 A (parallel contacts) (Serial contacts), rated voltage (III/2): 32 V, number of positions: 8, product range: TBUS8-25..., pitch: 2.54 mm, mounting: DIN rail mounting, locking: without, mounting method: without, type of packaging: packed in cardboard, Item with gold-plated contacts, bus connectors for connecting with electronics housings, 4 parallel contacts/4 serial contacts

Your advantages

• Up to four parallel and series contacts respectively for efficient signal and data transmission

Commercial data

Item number	1156781
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	AC09
Product key	ACHAGA
GTIN	4063151159849
Weight per piece (including packing)	7.25 g
Weight per piece (excluding packing)	6 g
Customs tariff number	85366990
Country of origin	PL



1156781

https://www.phoenixcontact.com/us/products/1156781

Technical data

Notes

	Recommendation	Material of contact pads for bus connector, galvanic gold (hard gold)
Pro	oduct properties	
	Product type	DIN rail connector
	Product family	TBUS8-25
	Number of positions	8
	Pitch	2.54 mm

Electrical properties

Nominal current I _N	6 A (parallel contacts)
Nominal voltage U _N	32 V
Rated voltage (III/2)	32 V
Rated surge voltage (III/2)	1.5 kV
Rated voltage (II/2)	32 V
Rated surge voltage (II/2)	1.5 kV

Material specifications

Material data - contact

Contact material	Cu alloy
Surface characteristics	gold-plated

Material data - housing

Color (Housing)	light gray (7035)
Insulating material	PA
Insulating material group	I
CTI according to IEC 60112	600
Flammability rating according to UL 94	V0

material specifications - connector

Color ()	()
----------	----

Dimensions

Pitch	2.54 mm
Width [w]	29.3 mm
Height [h]	37.15 mm
Length [I]	16.3 mm

Mounting

9	
Mounting type	DIN rail mounting

Environmental and real-life conditions



1156781

https://www.phoenixcontact.com/us/products/1156781

Ambient conditions

Ambient temperature (operation)	-40 °C 105 °C (dependent on the derating curve)
Ambient temperature (storage/transport)	-40 °C 55 °C
Relative humidity (storage/transport)	30 % 70 %
Ambient temperature (assembly)	-5 °C 100 °C

Electrical tests

Air clearances and creepage distances |

Specification	IEC 60664-1:2007-04
Insulating material group	I
Rated insulation voltage (III/2)	32 V
Rated surge voltage (III/2)	1.5 kV
minimum clearance value - non-homogenous field (III/2)	0.5 mm
minimum creepage distance (III/2)	0.53 mm
Rated insulation voltage (II/2)	32 V
Rated surge voltage (II/2)	1.5 kV
minimum clearance value - non-homogenous field (II/2)	0.5 mm
minimum creepage distance (II/2)	0.53 mm

Packaging specifications

Type of packaging	packed in cardboard
Outer packaging type	Carton



1156781

https://www.phoenixcontact.com/us/products/1156781

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/1156781

cUL Recognized Approval ID: E118976-20151204				
	Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
Power	29.9 V	4 A	-	-
Signal	29.9 V	4 A	-	-

UL Recognized Approval ID: E118976-2	UL Recognized Approval ID: E118976-20151204			
	Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
Power	29.9 V	6 A	-	-
Signal	29.9 V	4 A	-	-

cULus Recognized



1156781

https://www.phoenixcontact.com/us/products/1156781

Classifications

ECLASS

	ECLASS-11.0	27460201		
	ECLASS-12.0	27460201		
	ECLASS-13.0	27460201		
ETIM				
	ETIM 9.0	EC002637		
UNSPSC				
	UNSPSC 21.0	39121400		



1156781

https://www.phoenixcontact.com/us/products/1156781

Environmental product compliance

EU RoHS

20 100.10			
Fulfills EU RoHS substance requirements	Yes, No exemptions		
China RoHS			
Environment friendly use period (EFUP)	EFUP-E		
	No hazardous substances above the limits		
EU REACH SVHC			
REACH candidate substance (CAS No.)	No substance above 0.1 wt%		

Phoenix Contact 2025 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com