



Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.2 – .51 mm²**

Mating Tab Width: **4.75 mm [.187 in]**

Mating Tab Thickness: **.51 mm [.02 in]**

Features

Industry Standards

Compatible With Agency/Standards Products	UL, CSA
---	---------

Termination Features

Product Terminates To	Wire & Cable
-----------------------	--------------

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
Connection Capacity	Single

Mechanical Attachment

Wire Insulation Support	With
Mating Retention Type	Dimple
Extraction Force	6.8 kgf

Other

Line	Premier
EU RoHS Compliance	Compliant
EU ELV Compliance	Compliant



Packaging Features

Packaging Quantity	1000
Packaging Method	Loose Piece/Carton

Dimensions

Product Length	15 mm[.59 in]
Compatible Insulation Diameter Range	1.5 – 2.5 mm[.059 – .098 in]
Terminal Material Thickness	.3 mm[.012 in]
Wire Size	.2 – .51 mm²

Product Type Features

Insertion Force	Normal
-----------------	--------

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	4.75 mm[.187 in]
Mating Tab Thickness	.51 mm[.02 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Tin
Crimp Type	F-Crimp
Barrel Type	Open

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per



homogenous material. Also BFR/CFR/PVC Free

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 63699-1
ADAPTER 187 FASTON TPBR

TE Part # 61045-2
FASTON .187 SERIES (4.8 MM) TPBR

TE Part # 170141-2
187 FASTON, FLAG, REC., 20-16 AWG, TPBR

TE Part # 724678-1
DAHT 187 FASTON REC 24-20 ASSY

Also in the Series | FASTON 187

Crimp Terminal Housings(41)

Insertion & Extraction Tools(1)

Joints & Splices(1)


PCB Terminals(42)

Quick Disconnects(207)


Splices(1)



Customers Also Bought



TE Part #208652-1
SEALING CAP ASSY,SZ 17,CPC



TE Part #182661-1
CPC Cable Clamp Kit, Size 17, Large, UV




TE Part #182642-1
17-16 CPC PLUG




TE Part #182916-1
CPC SQ.FL.RCPT STD SEX



TE Part #66255-8
MALE CONTACT ASSY. (STRIP)




TE Part #2-87195-4
MOD IV RECP PLTE 15 DPLX




TE Part #60986-1
.058 DIA PIN RECPT L/P



TE Part #1623932-5
CFR50 5% 100K



TE Part #160773-6
PL LOOSE PIECE REC 0.5-1.5 MM2 PTPBR



TE Part #1-2350514-2
12POS TB HDR 90 DEG, PITCH 3.5 &TL 3.5mm

Documents

Product Drawings

187 FASTON,REC.,24-20 AWG,TPBR

Japanese

187 FASTON,REC.,24-20 AWG,TPBR

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_170203-2_B_c-170203-2-b.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_170203-2_B_c-170203-2-b.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_170203-2_B_c-170203-2-b.3d_stp.zip



English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

CRIMPING OF 187 SERIES FASTON RECEPTACLE

Japanese

Application Specification

Japanese

Agency Approvals

UL Report

English