TE Internal #: 160252-2

Closed Ring Tongue Terminal, 20 – 15 AWG, #8 / M4 Stud, 4.3 mm

[.169 in] Stud Diameter, Open Barrel, Straight, Tin Plating,

Uninsulated

View on TE.com >



Terminals & Splices > Ring Terminals











Ring Terminal Product Type: Closed Ring Tongue Terminal

Wire Size: 1021 – 3256 CMA

Stud Size: #8, M4

Features

Configuration Features	
Number of Holes	1
Body Features	
Product Weight	.331 g
Mechanical Attachment	
Wire Insulation Support	With
Industry Standards	
Government Qualified Terminal	No
Packaging Features	
Packaging Quantity	15000
Packaging Method	Strip/Reel
Contact Features	
Contact Base Material	Brass

Straight

Tin

Terminal Orientation

Terminal Plating Material



Contact Underplating Material	None
Dimensions	
	.098 in
Wire Size	1021 – 3256 CMA
Stud Diameter	4.3 mm[.169 in]
Tongue Thickness	.61 mm[.024 in]
Product Length	12.45 mm[.49 in]
Barrel Inside Diameter	1.9 mm, 2.79 mm[.075 in][.11 in]
Compatible Insulation Diameter (Max)	3.4 mm[.134 in]
Compatible Insulation Diameter Range	2.5 – 3.4 mm[.098 – .134 in]
Product Type Features	
Shape Description	Circular/Oval
Ring Terminal Product Type	Closed Ring Tongue Terminal
Stud Size	#8, M4
Sealable	No
Sealable	
Compatible With Discrete Wire Type	Stranded
Compatible With Discrete Wire Type	Stranded
Compatible With Discrete Wire Type Wire Insulation Support Retention Type	Stranded
Compatible With Discrete Wire Type Wire Insulation Support Retention Type Usage Conditions	Stranded Insulation Support
Compatible With Discrete Wire Type Wire Insulation Support Retention Type Usage Conditions Insulation Option	Stranded Insulation Support Uninsulated
Compatible With Discrete Wire Type Wire Insulation Support Retention Type Usage Conditions Insulation Option Operating Temperature Range	Stranded Insulation Support Uninsulated
Compatible With Discrete Wire Type Wire Insulation Support Retention Type Usage Conditions Insulation Option Operating Temperature Range Operation/Application	Stranded Insulation Support Uninsulated -40 – 110 °C[-40 – 230 °F]
Compatible With Discrete Wire Type Wire Insulation Support Retention Type Usage Conditions Insulation Option Operating Temperature Range Operation/Application Compatible With Wire Base Material	Stranded Insulation Support Uninsulated -40 – 110 °C[-40 – 230 °F]

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241)



	Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts













Customers Also Bought
























Documents

Product Drawings

RING TONGUE IS AUTOMATIC 0.5-1.43MM2TPBR

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_160252-2_O.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_160252-2_O.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_160252-2_O.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Closed Ring Tongue Terminal, 20 – 15 AWG, #8 / M4 Stud, 4.3 mm [.169 in] Stud Diameter, Open Barrel, Straight, Tin Plating, Uninsulated



Application Specification

English