




Connectors > PCB Connectors > Card Edge Connectors > PCI & PCI Express Connectors



Connector System: **Board-to-Board**

Number of Positions: **120**

Centerline (Pitch): **1.27 mm [.05 in]**

Termination Post & Tail Length: **3.18 mm [.125 in]**

Contact Mating Area Plating Material Thickness: **[ 30 µin ]**

Features

Mechanical Attachment

Connector Mounting Type	Board Mount
-------------------------	-------------

Electrical Characteristics

Operating Voltage	203 VAC
-------------------	---------

Industry Standards

Bus Type	PCI
----------	-----

Packaging Features

Packaging Method	Box & Carton
Packaging Quantity	35

Dimensions

PCB Thickness (Accepted)	1.57 mm[.062 in]
Connector Length	84.84 mm[3.34 in]
Connector Height	13.97 mm[.55 in]
Connector Width	8.8 mm[.346 in]

Body Features

--	--



Product Weight	12.58 g
Primary Product Color	Natural

Contact Features

Contact Current Rating (Max)	1.1 A
PCB Contact Termination Area Plating Material Thickness	2.537 µm
Contact Underplating Material	Nickel
Contact Mating Area Plating Material	Gold
Contact Base Material	Phosphor Bronze
PCB Contact Termination Area Plating Material	Tin
	30 µin

Termination Features

Termination Method to PCB	Through Hole - Solder
Termination Post & Tail Length	3.18 mm[.125 in]

Housing Features

Housing Material	High Temperature Thermoplastic
Centerline (Pitch)	1.27 mm[.05 in]

Configuration Features

Number of PCB Mount Retention Features	2
Number of Positions	120
PCB Mount Orientation	Vertical
Ejector	Without

Product Type Features

Connector & Contact Terminates To	Printed Circuit Board
Connector System	Board-to-Board

Usage Conditions

Operating Temperature Range	-55 – 85 °C[-67 – 185 °F]
-----------------------------	---------------------------

Operation/Application

Circuit Application	Signal
---------------------	--------

Other

EU RoHS Compliance	Compliant
EU ELV Compliance	Compliant



Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 5-2337939-4  
PCIE GEN4 CON,SMT,164POS,30u", MYLAR,HT



TE Part # 5145154-1  
CONNECTOR, 60 DUAL POSITION, .



TE Part # 1734774-1  
PCI EXP 3.1L 36 POS WHT G/F

Customers Also Bought



TE Part #1-1871468-2 DYNAMIC 1200S HDR ASSY V 2P X BLACK GOLD	TE Part #770232-1 CMNL IDC COVER	TE Part #770156-3 4P CMNL IDC PLUG 18AWG ORG V2	TE Part #171825-5 5 POS EIS POST HDR
TE Part #1473567-4 RITS CONN.HDR ASSY 4ROW 4P	TE Part #1-2227303-2 CAGE ASSEMBLY, SFP, .071 TAIL	TE Part #1-2301997-0 RJ45 JACK INT.MAG. 1GB LED 2X1	TE Part #2143451-2 SFP+ 1X2 Assy, Sldr Tail, T&R
TE Part #2265305-1 CABLE ASSY, MM TO SUB D	TE Part #5-1393704-8 V23552A2255S 3=SIPAC FL 2SU		

Documents

Product Drawings

STANDARD EDGE .050 SERIES 60 DUAL ASSY

English

CAD Files

Customer View Model

ENG\_CVM\_CVM\_5145154-8\_B.2d\_dxf.zip

English

3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_5145154-8\_B.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_5145154-8\_B.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications



Application Specification

English