SFP28 | XFP

TE Internal #: 2303074-1

XFP, Cage Assembly, Sealable, Signal, Operating Temperature Range -10 – 70 °C [14 – 158 °F], Data Rate (Max) 10 Gb/s, 1 Ports

View on TE.com >



Connectors > Pluggable IO Connectors & Cages > XFP Cage Assemblies and Kits











Form Factor: XFP

Pluggable I/O Product Type: Cage Assembly

Sealable: Yes

Circuit Application: Signal

Operating Temperature Range: -10 - 70 °C [14 - 158 °F]

All XFP Cage Assemblies and Kits (22)

Features

Industry Standards

UL Flammability Rating	UL 94V-0
Contact Features	
Contact Mating Area Plating Material	Gold
Termination Features	
Termination Method to PCB	Through Hole - Press-Fit
Termination Post & Tail Length	2.05 mm
Dimensions	
Product Width	22 mm
Product Length	64.03 mm
Housing Features	
Housing Material	LCP (Liquid Crystal Polymer)

Nickel Silver Alloy

Cage Material



Mechanical Attachment

PCB Mounting Style	Double-Sided (Belly-to-Belly)
Body Features	
Cage Plating Material	Tin
Primary Product Material	Aluminum
Packaging Features	
Packaging Method	Box & Tray
Operation/Application	
Heat Sink Compatible	Yes
Circuit Application	Signal
Product Type Features	
Cage Type	Single
Form Factor	XFP
Pluggable I/O Product Type	Cage Assembly
Sealable	Yes
Sealable Configuration Features	Yes
	Yes 1
Configuration Features	
Configuration Features Number of Ports	1
Configuration Features Number of Ports Port Matrix Configuration	1
Configuration Features Number of Ports Port Matrix Configuration Electrical Characteristics	1 1 x 1
Configuration Features Number of Ports Port Matrix Configuration Electrical Characteristics Data Rate (Max)	1 1 x 1
Configuration Features Number of Ports Port Matrix Configuration Electrical Characteristics Data Rate (Max) Usage Conditions	1 1 x 1 10 Gb/s
Configuration Features Number of Ports Port Matrix Configuration Electrical Characteristics Data Rate (Max) Usage Conditions Operating Temperature Range	1 1 x 1 10 Gb/s
Configuration Features Number of Ports Port Matrix Configuration Electrical Characteristics Data Rate (Max) Usage Conditions Operating Temperature Range Other	1 1 x 1 10 Gb/s -10 - 70 °C[14 - 158 °F]
Configuration Features Number of Ports Port Matrix Configuration Electrical Characteristics Data Rate (Max) Usage Conditions Operating Temperature Range Other Included Lightpipe	1 1 x 1 10 Gb/s -10 - 70 °C[14 - 158 °F] No

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant	
------------------------------	-----------	--



EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Also in the Series | XFP





Pluggable IO Connectors & Cages(25)





Customers Also Bought





















Documents

Product Drawings

XFP CAGE ASSEMBLY, W/O INTERMEDIATE GSKT

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2303074-1_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2303074-1_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2303074-1_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

XFP, Cage Assembly, Sealable, Signal, Operating Temperature Range -10 – 70 °C [14 – 158 °F], Data Rate (Max) 10 Gb/s, 1 Ports



Product Specifications

Application Specification

English