

VIP-3/SC/D37SUB/M/LED - Termination board

2322171

<https://www.phoenixcontact.com/us/products/2322171>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



VARIOFACE module, with screw connections and D-SUB pin strip, for mounting on NS 35 rails, with LED, 37-pos.

Your advantages

- 9-pos. ... 50-pos.
- Metal foot
- In accordance with IEC 60603-13
- Screw connection
- 1:1 connection
- In accordance with IEC 60603-13

Commercial data

Item number	2322171
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	C423
Product key	CK2112
Catalog page	Page 571 (C-5-2017)
GTIN	4046356451796
Weight per piece (including packing)	193.3 g
Weight per piece (excluding packing)	193.1 g
Customs tariff number	85366990
Country of origin	US

VIP-3/SC/D37SUB/M/LED - Termination board

2322171

<https://www.phoenixcontact.com/us/products/2322171>



Technical data

Product properties

Product type	Interface module
Product family	VARIOFACE Professional
Number of positions	37

Insulation characteristics

Overvoltage category	II
Pollution degree	2

Electrical properties

Nominal voltage U_N	24 V DC
Max. current carrying capacity per branch	2.5 A

Connection data

Field level

Connection in acc. with standard	IEC / EN
Connection method	Screw connection
Stripping length	8 mm
Screw thread	M3
Conductor cross section rigid	0.2 mm ² ... 4 mm ²
Conductor cross section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross section AWG	24 ... 12
Tightening torque	0.5 Nm ... 0.6 Nm

Controller level

Connection method	D-SUB pin strip
Number of connections	1
Number of positions	37

Signaling

Status display	LED
Status display present	Yes

Dimensions

Item dimensions

Width	72.7 mm
Height	69 mm
Depth	62 mm

Material specifications

Color	gray (RAL 7042)
Flammability rating according to UL 94	V0

VIP-3/SC/D37SUB/M/LED - Termination board

2322171

<https://www.phoenixcontact.com/us/products/2322171>



Housing insulation material

Polyamide PA non-reinforced

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

Standards and regulations

Standards/regulations	IEC 60664
	DIN EN 50178

Mounting

Mounting type	DIN rail mounting
Mounting position	any

Notes

Notes on operation	For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met.
--------------------	--

VIP-3/SC/D37SUB/M/LED - Termination board


2322171

<https://www.phoenixcontact.com/us/products/2322171>



Drawings

Dimensional drawing




VIP-3/SC/D37SUB/M/LED - Termination board

2322171

<https://www.phoenixcontact.com/us/products/2322171>



Circuit diagram



VIP-3/SC/D37SUB/M/LED - Termination board

2322171

<https://www.phoenixcontact.com/us/products/2322171>



Approvals

ⓘ To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2322171>

	CSA	Approval ID: 2122203		
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	24 V	2 A	28 - 12	-

	cUL Recognized	Approval ID: E238705		
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	24 V	2 A	30 - 12	-

	UL Recognized	Approval ID: E238705		
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	24 V	2 A	30 - 12	-

	CSAus	Approval ID: 2122203		
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	24 V	2 A	28 - 12	-

cULus Recognized

cCSAus

VIP-3/SC/D37SUB/M/LED - Termination board

2322171

<https://www.phoenixcontact.com/us/products/2322171>



Classifications

ECLASS

ECLASS-11.0	27141152
ECLASS-13.0	27141152
ECLASS-12.0	27141152

ETIM

ETIM 9.0	EC002780
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

VIP-3/SC/D37SUB/M/LED - Termination board

2322171

<https://www.phoenixcontact.com/us/products/2322171>



Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c), 7(c)-I

China RoHS

Environment friendly use period (EFUP)	EFUP-50
An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.	

EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	1ddeff14-e0ad-482e-889d-4da51cae6ef9

Phoenix Contact 2025 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA

586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com