

TE Internal #: 2287076-2

CFP2, Cage Assembly, Signal, Operating Temperature Range -55 –

85 °C [-67 – 185 °F], Data Rate (Max) 56 Gb/s, 2 Ports, Port Matrix

Configuration 1 x 2

View on TE.com >



#### Connectors > Pluggable IO Connectors & Cages











Form Factor: CFP2

Pluggable I/O Product Type: Cage Assembly

Sealable: No

Circuit Application: Signal

Contact Current Rating (Max)

Operating Temperature Range: -55 - 85 °C [ -67 - 185 °F ]

### **Features**

#### **Contact Features**

Termination Features	
Termination Method to PCB	Through Hole - Press-Fit
Dimensions	
Product Width	87.84 mm

.5 A

Froduct Width	07.04 [[[[[
Product Length	93.2 mm
PCB Thickness (Recommended)	3 mm[.118 in]

### **Body Features**

Primary Product Plating Material	Nickel
Primary Product Material	Aluminum Alloy

### **Packaging Features**

Packaging Method	Box & Tray	
------------------	------------	--

## Operation/Application

Heat Sink Compatible Yes
--------------------------



Circuit Application	Signal
Product Type Features	
Cage Type	Ganged
Form Factor	CFP2
Pluggable I/O Product Type	Cage Assembly
Sealable	No
Configuration Features	
Number of Ports	2
Port Matrix Configuration	1 x 2
Electrical Characteristics	
Data Rate (Max)	56 Gb/s
Usage Conditions	
Operating Temperature Range	-55 – 85 °C[-67 – 185 °F]
Other	
Included Lightpipe	No
EMI Containment Feature Type	Internal/External EMI Springs
EU RoHS Compliance	Compliant
EU ELV Compliance	Compliant

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts





# Customers Also Bought





















#### **Documents**

### **Product Drawings**

CFP2 CAGE ASSEMBLY, 1X2

English

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_2287076-2\_1.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2287076-2\_1.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2287076-2\_1.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

## **Product Specifications**

**Application Specification** 

English