CII

TE Internal #: 1-1617005-0

General Purpose Power Relay, DC, Non-Polarized, Monostable, 2 Form C DPDT-CO, 10 A Contact Rating, 26.5 VDC Coil Voltage,

2.34 W Coil Power

View on TE.com >



Relays & Contactors > Electromechanical Relays



Relay & Contactor Type: General Purpose Power Relay

Current Type: DC

Coil Magnetic System: Non-Polarized, Monostable

Contact Arrangement: 2 Form C DPDT-CO

Contact Current Rating: 10 A

Features

Contact Features	
Contact Material	Silver Cadmium Oxide
Usage Conditions	
Operating Temperature Range	-65 – 125 °C
Environmental Ambient Temperature (Max)	125 °C[257 °F]
Mechanical Attachment	
Product Mounting Feature Type	Mounting Studs
Product Mount Type	Panel Mount
Electrical Characteristics	
Coil Resistance	300 Ω
Contact Switching Voltage (Max)	28 VDC
Contact Current Rating	10 A
Coil Voltage Rating	26.5 VDC
Coil Power Rating DC	2.34 W
Operation/Application	
Vibration Resistance	20G's, 10 – 2000Hz
Shock Resistance	50G's, 11ms

DC

Current Type



Coil Magnetic System	Non-Polarized, Monostable
331111149113131	rion rolanzod/monocabio

Product Type Features

Relay & Contactor Type	General Purpose Power Relay

Configuration Features

Contact Arrangement	2 Form C DPDT-CO

Body Features

Enclosure Type Hermetically Sealed

Termination Features

Main Termination & Connection Type	Solder Hook Terminals
Coil Termination & Connection Type	Solder Hook Terminals

Other

EU RoHS Compliance	Not Compliant
EU ELV Compliance	Not Compliant

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not lead free process capable

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An



Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts



Customers Also Bought







CMC-0553-6-9









TE Part #2-1532186-9 M83513/03-H12C, MCKS-C2-B-100P6Q9-36.0



TE Part #9-1617784-2 FCB-205-0117M=M83536/1-017M







Documents

Product Drawings
B07E932BC4-0262 = MS27245-5

English

General Purpose Power Relay, DC, Non-Polarized, Monostable, 2 Form C DPDT-CO, 10 A Contact Rating, 26.5 VDC Coil Voltage, 2.34 W Coil Power



Datasheets & Catalog Pages

5-1773450-5_sec1_07

English

RELAY

English