SPLICE

TE Internal #: 41974

Pigtail Splice / Thru Splice, 20 – 15 AWG, .51 – 1.5 mm² Wire, Serrated, 1000 – 3200 CMA, Brass, 3 Serration, Length 3.81 mm [.15


in], Reel, SPLICE

View on TE.com >



Terminals & Splices > Splices











Splice Type: Pigtail Splice, Thru Splice

Wire Size: .51 – 1.5 mm²

Sealable: No

Splice Features: Serrated

Features

Packaging Features

Packaging Quantity	33000
Packaging Method	Reel

Body Features

Product Weight	.118 g
Splice Features	Serrated

Product Type Features

Splice Type	Pigtail Splice, Thru Splice
Sealable	No
Compatible With Discrete Wire Type	Solid, Stranded
Wire Insulation Support Retention Type	Non-Insulation Support

Configuration Features

Number of Serrations	3
Compatible With Wire & Cable Type	Discrete Wire

Contact Features



Contact Base Material	Brass
Barrel Type	Open
Mechanical Attachment	
Wire Insulation Support	Without
Dimensions	
Wire Size	1000 – 3200 CMA
Terminal Material Thickness	.51 mm[.02 in]
Product Length	3.81 mm[.15 in]
Usage Conditions	
Insulation Option	Uninsulated
Operating Temperature Range	-40 - 110 °C[-40 - 230 °F]
Operation/Application	
Compatible With Wire Base Material	Copper
Industry Standards	
Government Qualified Splice	No
Other	
EU RoHS Compliance	Compliant

Product Compliance

EU ELV Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Compliant

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts











Also in the Series | SPLICE





Customers Also Bought





TE Part #640911-1
RECEPT,PIDG FASTON 22-18 205



















Documents

Product Drawings

SPLICE 1000-3200 CMA BR

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_41974_AP_c-41974-ap.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_41974_AP_c-41974-ap.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_41974_AP_c-41974-ap.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Pigtail Splice / Thru Splice, 20 – 15 AWG, .51 – 1.5 mm² Wire, Serrated, 1000 – 3200 CMA, Brass, 3 Serration, Length 3.81 mm [.15 in], Reel, SPLICE



Application Specification

English

Agency Approvals

CSA Certificate

English