1-5145165-2 ACTIVE

TE Internal #: 1-5145165-2

Board-to-Board, 184 Position, 1.27 mm [.05 in] Centerline, Vertical, Natural, Height 13.97 mm [.55 in], PCI & PCI Express Connectors

View on TE.com >



Connectors > PCB Connectors > Card Edge Connectors > PCI & PCI Express Connectors



Connector System: Board-to-Board

Number of Positions: 184

Centerline (Pitch): 1.27 mm [.05 in]

Termination Post & Tail Length: 3.56 mm [.14 in]

Contact Mating Area Plating Material Thickness: [30 µin]

Features

Mechanical Attachment

Connector Mounting Type	Board Mount
Electrical Characteristics	
Operating Voltage	203 VAC
Industry Standards	
Bus Type	PCI
Packaging Features	
Packaging Method	Box
Packaging Quantity	35
Dimensions	
PCB Thickness (Accepted)	1.57 mm[.062 in]
Connector Length	128 mm[5.039 in]
Connector Height	13.97 mm[.55 in]
Connector Width	8.88 mm[.35 in]
Body Features	



Product Weight	12.58 g
Primary Product Color	Natural
Contact Features	
PCB Contact Termination Area Plating Material Thickness	2.54 μm
Contact Underplating Material	Nickel
Contact Mating Area Plating Material	Gold
Contact Base Material	Phosphor Bronze
PCB Contact Termination Area Plating Material	Tin
	30 μin
Termination Features	
Termination Method to PCB	Through Hole - Solder
Termination Post & Tail Length	3.56 mm[.14 in]
Housing Features	
Housing Material	High Temperature Thermoplastic
Centerline (Pitch)	1.27 mm[.05 in]
Configuration Features	
Number of PCB Mount Retention Features	3
Number of Positions	184
PCB Mount Orientation	Vertical
Ejector	Without
Product Type Features	
Connector & Contact Terminates To	Printed Circuit Board
Connector & Contact Terminates To Connector System	Printed Circuit Board Board-to-Board
Connector System	
Connector System Usage Conditions	Board-to-Board
Connector System Usage Conditions Operating Temperature Range	Board-to-Board
Connector System Usage Conditions Operating Temperature Range Operation/Application	Board-to-Board -55 – 85 °C[-67 – 185 °F]
Connector System Usage Conditions Operating Temperature Range Operation/Application Circuit Application	Board-to-Board -55 – 85 °C[-67 – 185 °F]

Product Compliance



For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts







Customers Also Bought





















Documents

Product Drawings

CONNECTOR ASSEMBLY, DUAL POSITIONS, .050

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-5145165-2_D.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-5145165-2_D.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-5145165-2_D.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Board-to-Board, 184 Position, 1.27 mm [.05 in] Centerline, Vertical, Natural, Height 13.97 mm [.55 in], PCI & PCI Express Connectors



Application Specification

English

Agency Approvals

UL Report

English