1-1546306-0 ACTIVE

Buchanan

TE Internal #: 1-1546306-0

10 Position Barrier Strip, Dual Barrier, Wire-to-Wire, 9.53 mm [.375 in] Centerline, 2 Row, 300 V, 22 – 12 AWG, .3 – 3 mm² Wire, Wire &

Cable

View on TE.com >




Connectors > Terminal Blocks & Strips > Barrier Strips











Number of Positions: 10

Barrier Strip Style: **Dual Barrier**Connector System: **Wire-to-Wire**Centerline (Pitch): **9.53 mm [.375 in]**

Number of Rows: 2

Features

Industry Standards

Industry Standards	
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Method	Carton
Packaging Quantity	100
Operation/Application	
Circuit Application	Power
Mechanical Attachment	
Top Termination Type	Wire Clamp Combo Head
Mounting Options	End Mounting Ears
Screw Plating Material	Nickel

6-32

Combo Phil-Slot

Panel Mount

Thread Size

Screw Head Type

Connector Mounting Type



Contact Features	
Contact Base Material	Brass
Contact Current Rating (Max)	20 A
Dimensions	
Product Length	112 mm[4.41 in]
Wire Size	22 – 12 AWG
Housing Features	
Housing Material	Thermoplastic
Centerline (Pitch)	9.53 mm[.375 in]
Product Type Features	
Block Style	Non-Feed Through
Connector System	Wire-to-Wire
Connector & Contact Terminates To	Wire & Cable
Body Features	
Quick Connect Tab Plating Material	Tin
Primary Product Color	Black
Product Orientation	Vertical
Barrier Strip Style	Dual Barrier
Configuration Features	
Number of Levels	1
Number of Positions	10
Number of Rows	2
Electrical Characteristics	
Operating Voltage	300 V
Usage Conditions	
Usage Conditions Operating Temperature Range	-40 - 120 °C[-40 - 248 °F]
	-40 – 120 °C[-40 – 248 °F]
Operating Temperature Range	-40 – 120 °C[-40 – 248 °F] Compliant

Product Compliance

For compliance documentation, visit the product page on TE.com>



EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Customers Also Bought





TE Part #5745395-2 HD-20 RCPT 9P RA 318 FFSCRLK



TE Part #5767081-1 MICT,REC,038,ASY,PDNI,BARBLESS



TE Part #1-2176429-3 MPT100 10R 5%





TE Part #442055-000 D-436-0154



TE Part #ZPF00000000001197 097-0013-16







Documents

Product Drawings

10P.374" DR BARRIER STRIP

English

CAD Files

Customer View Model

ENG_CVM_CVM_1-1546306-0_K1.3d_stp.zip

English

Customer View Model

ENG_CVM_CVM_1-1546306-0_K1.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-1546306-0_K1.3d_igs.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

10 Position Barrier Strip, Dual Barrier, Wire-to-Wire, 9.53 mm [.375 in] Centerline, 2 Row, 300 V, 22 – 12 AWG, .3 – 3 mm² Wire, Wire & Cable



1-1773458-2_BARRIER_STRIPS_QUICK_REFERENCE_GUIDE

English

Agency Approvals

UL

English