



Connectors > PCB Connectors > Wire-to-Board Connectors > FFC, FPC & Ribbon Connectors > Ribbon Cable Connectors >

Female-on-Board Connector, Top Entry



Connector System: **Board-to-Board**

Number of Positions: **18**

Centerline (Pitch): **1.27 mm [.05 in]**

PCB Mount Retention: **Without**

PCB Mount Orientation: **Vertical**

[All Female-on-Board Connector, Top Entry \(67\)](#)

Features

Electrical Characteristics

|                       |         |
|-----------------------|---------|
| Operating Voltage     | 100 VDC |
| Insulation Resistance | 1000 MΩ |

Industry Standards

|                                             |            |
|---------------------------------------------|------------|
| Compatible With Agency/Standards Products   | UL         |
| UL Rating                                   | Recognized |
| UL Flammability Rating                      | UL 94V-0   |
| Compatible With Approved Standards Products | UL E28476  |

Packaging Features

|                    |      |
|--------------------|------|
| Packaging Quantity | 900  |
| Packaging Method   | Reel |

Operation/Application

|                        |                |
|------------------------|----------------|
| Solder Process Feature | Board Standoff |
| Circuit Application    | Signal         |

Contact Features

|                                                      |        |
|------------------------------------------------------|--------|
| Contact Underplating Material                        | Nickel |
| PCB Contact Termination Area Plating Material Finish | Matte  |



|                                                         |                               |
|---------------------------------------------------------|-------------------------------|
| Contact Mating Area Plating Material Thickness          | 3 – 5 µm[118.11 – 196.85 µin] |
| Contact Shape & Form                                    | Dual Beam                     |
| PCB Contact Termination Area Plating Material Thickness | 3 – 5 µm[118.11 – 196.85 µin] |
| Contact Mating Area Plating Material                    | Tin                           |
| Contact Base Material                                   | Phosphor Bronze               |
| PCB Contact Termination Area Plating Material           | Tin                           |
| Contact Type                                            | Socket                        |
| Contact Current Rating (Max)                            | 1.5 A                         |

Body Features

|                       |          |
|-----------------------|----------|
| Daisy Chain           | Without  |
| Primary Product Color | Red      |
| Connector Profile     | Standard |

Dimensions

|                             |                  |
|-----------------------------|------------------|
| PCB Thickness (Recommended) | 1.6 mm[.062 in]  |
| Connector Height            | 6.9 mm[.27 in]   |
| Connector Length            | 27.4 mm[1.07 in] |
| Row-to-Row Spacing          | 2 mm[.059 in]    |

Termination Features

|                                               |                 |
|-----------------------------------------------|-----------------|
| Rectangular Termination Post & Tail Width     | .75 mm[.029 in] |
| Rectangular Termination Post & Tail Thickness | .25 mm[.01 in]  |
| Termination Post & Tail Length                | 5.3 mm[.208 in] |
| Termination Method to PCB                     | Surface Mount   |

Mechanical Attachment

|                                       |                  |
|---------------------------------------|------------------|
| Contact Retention Type Within Housing | Press-Fit        |
| Mating Alignment                      | With             |
| PCB Mount Alignment                   | Without          |
| PCB Mount Retention                   | Without          |
| Mating Alignment Type                 | Polarization     |
| Mating Retention                      | With             |
| Mating Retention Type                 | Contact Friction |
| Connector Mounting Type               | Board Mount      |

Housing Features

|  |  |
|--|--|
|  |  |
|--|--|



|                       |                 |
|-----------------------|-----------------|
| Mating Entry Location | Top             |
| Housing Material      | PA 4.6          |
| Centerline (Pitch)    | 1.27 mm[.05 in] |

Product Type Features

|                                    |                       |
|------------------------------------|-----------------------|
| Connector Product Type             | Connector Assembly    |
| Ribbon Cable Connector Type        | Female-on-Board       |
| Ribbon Cable Connector Header Type | Shrouded              |
| Connector System                   | Board-to-Board        |
| Connector & Housing Type           | Receptacle            |
| Connector & Contact Terminates To  | Printed Circuit Board |

Configuration Features

|                       |          |
|-----------------------|----------|
| Number of Positions   | 18       |
| PCB Mount Orientation | Vertical |
| Number of Rows        | 2        |

Usage Conditions

|                             |                            |
|-----------------------------|----------------------------|
| Operating Temperature Range | -40 – 105 °C[-40 – 221 °F] |
|-----------------------------|----------------------------|

Other

|                    |           |
|--------------------|-----------|
| EU RoHS Compliance | Compliant |
| EU ELV Compliance  | Compliant |

Product Compliance

For compliance documentation, visit the product page on TE.com>

|                                               |                                                                                                                                 |
|-----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| EU RoHS Directive 2011/65/EU                  | Compliant                                                                                                                       |
| EU ELV Directive 2000/53/EC                   | Compliant                                                                                                                       |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold                                                                                         |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2024 (241)<br>Candidate List Declared Against: JUNE 2024 (241)<br>Does not contain REACH SVHC |
| Halogen Content                               | Not Low Halogen - contains Br or Cl > 900 ppm.                                                                                  |
| Solder Process Capability                     | Reflow solder capable to 260°C                                                                                                  |

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # CAT-M5833-M2934  
Male-on-Board Connector, Micro-MaTch

TE Part # 1-338095-8  
18P. MICRO-MATCH COSI HSG

TE Part # CAT-M5833-M2934A  
Male-on-Wire Connector, Micro-MaTch

Also in the Series | Micro-MaTch Industrial

Board-In Connectors(20)

Connector Contacts(4)

Insertion & Extraction Tools(1)

Pluggable I/O Cable Assemblies(52)

Ribbon Cable Connectors(183)

Customers Also Bought



TE Part #4-1393789-3  
V23079D2001B301

TE Part #1-1623819-4  
SBL4 R051 5%

TE Part #2301994-9  
RJ45 JACK INT.MAG. 10/100 LED 1X1

TE Part #1-2176340-7  
CRGCQ 0603 470R 5%

TE Part #5-2176330-4  
CRGP 2010 270K 1%

TE Part #3-2176381-1  
RQ 0805 25K5 0.1% 10PPM 5K RL

TE Part #1-215079-8  
MICRO-MATCH FOB 18P

TE Part #4-160968-2  
CABLE TY 134X2.6 BLACK

TE Part #124045-E  
SMCB 50 F AB VV 6-03 CLHD \* H007  
137 E00

TE Part #5-1768034-7  
LEB-A4PM-X

Documents

Product Drawings  
MICRO-MATCH SMD FTE

English

CAD Files

3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_1-338069-8\_K.2d\_dxf.zip

English

Customer View Model

ENG\_CVM\_CVM\_1-338069-8\_K.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_1-338069-8\_K.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Datasheets & Catalog Pages



Micro-MaTch Catalog

English

Centerline Micro-Match Connector Series

English

---

Product Specifications

Application Specification

English