

TE Internal #: 40660

Closed Ring Tongue Terminal, 18 – 14 AWG, #8 / M4 Stud, 4.34

mm [.171 in] Stud Diameter, Open Barrel, Straight, Unplated

Plating, Uninsulated

View on TE.com >



Terminals & Splices > Ring Terminals











Ring Terminal Product Type: Closed Ring Tongue Terminal

Wire Size: 1624 – 4106 CMA

Stud Size: #8, M4

Features

Configuration Features	
Number of Holes	1
Body Features	
Product Weight	.864 g
Mechanical Attachment	
Wire Insulation Support	With
Industry Standards	
Government Qualified Terminal	No
Packaging Features	
Packaging Features Packaging Quantity	11000
	11000 Strip/Reel
Packaging Quantity	
Packaging Quantity Packaging Method	

Straight

Unplated

Terminal Orientation

Terminal Plating Material



Contact Underplating Material	None
Dimensions	
	.1 in
Wire Size	1624 – 4106 CMA
Stud Diameter	4.34 mm[.171 in]
Tongue Thickness	.76 mm[.03 in]
Product Length	19.81 mm[.78 in]
Barrel Inside Diameter	2.92 mm, 1.52 mm[.06 in][.115 in]
Compatible Insulation Diameter (Max)	3.56 mm[.14 in]
Compatible Insulation Diameter Range	2.54 – 3.56 mm[.1 – .14 in]
Product Type Features	
Shape Description	Circular/Oval
Ring Terminal Product Type	Closed Ring Tongue Terminal
Stud Size	#8, M4
Sealable	No
Compatible With Discrete Wire Type	Stranded
Wire Insulation Support Retention Type	Insulation Support
Usage Conditions	
Insulation Option	Uninsulated
Operating Temperature Range	-40 - 110 °C[-40 - 230 °F]
Operation/Application	
Compatible With Wire Base Material	Copper
Other	
EU RoHS Compliance	Compliant
EU ELV Compliance	Compliant

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241)



Candidate List Declared Against: JUNE 2024 (241)

Does not contain REACH SVHC

Halogen Content Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

Compatible Parts



TE Part # 60394-1 RING TERMINAL 20-16 AWG BR



TE Part # 2151370-1 OCEAN_2.0_Applicator-E-130F180F-



TE Part # 2151372-2 OCEAN-2.0-APPLICATOR-S-070F130O-RSA



TE Part # 2151370-2 OCEAN_2.0_Applicator-E-130F180F-



TE Part # 42933-2 RING TERMINAL 20-16 AWG TPBR



TE Part # 60390-1 SPADE CRIMP 20-16 AWG BR




OCEAN_2.0_SPARE_PART_KIT-130F180F







Customers Also Bought





















Documents

Product Drawings

RING 164(4.17 MM) TERMINAL 18-14 AWG BR

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_40660_AW_c-40660-aw.2d_dxf.zip

Closed Ring Tongue Terminal, 18 – 14 AWG, #8 / M4 Stud, 4.34 mm [.171 in] Stud Diameter, Open Barrel, Straight, Unplated Plating, Uninsulated



English

Customer View Model

ENG_CVM_CVM_40660_AW_c-40660-aw.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_40660_AW_c-40660-aw.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English